

216.1637

SPINA MOBILE

16A 3P+N+T 6h 346-415V 50Hz 60Hz Morsetti a vite



Certificati

TECHDATA		NORME E LEGGI	
Serie commerciale	Serie EUREKA	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Tipologia prodotto	SPINA MOBILE	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Descrizione sintetica	SPINA MOBILE		
Tipo installazione	PORTATILE		
Corrente nominale	16A	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Poli	3P+N+T		
Riferimento Orario	6h		
Tensione nominale (range)	250-400V		
Tensione nominale	346-415V		
Frequenza d'impiego	60Hz		
Frequenza d'impiego	50Hz		
Colore	ROSSO		
Materiale	TERMOPLASTICO		
Grado di protezione generico	Stagno all'immersione		
Grado di protezione IP	IP66/IP67		
Grado di protezione IK	IK07		
Tipo di uscite disponibili	DIRITTA		
Morsetti	Morsetti a vite		

Materiale di contatto	CuZn (ottone)
Trattamento superficiale cont.	Nichelato
Uscita cavo	PRESSACAVO