

Scheda tecnica prodotto

21 feb 2022 18:41



247.812597

SPINA DA INCASSO

125A 3P+N+T 6h 346-415V 50/60Hz

145X145MM Morsetti a vite

Certificati

TECHDATA		NORME E LEGGI	
Tipologia prodotto	SPINA DA INCASSO	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Serie commerciale	Serie EUREKA-MIL	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Descrizione sintetica	SPINA DA INCASSO		
Tipo installazione	INCASSO		
Corrente nominale	125A	EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Poli	3P+N+T	EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Riferimento Orario	6h		
Tensione nominale (range)	250-400V		
Tensione nominale	346-415V	EN 60309-1/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Frequenza d'impiego	50/60Hz	EN 60309-2/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Colore	ROSSO		
Materiale	TERMOPLASTICO	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Grado di protezione generico	Stagno all'immersione		
Grado di protezione IP	IP67		
Tipo di uscite disponibili	A SQUADRA		
Morsetti	Morsetti a vite		
Materiale di contatto	CuZn (ottone)		
Trattamento superficiale cont.	Nichelato		

Flangia

145X145MM