


# 506.M1679

## PRESA INTERBLOCCATA

16A 3P+N+T 4h 100-130V 50Hz 60Hz  
136X125MM\_PAR Morsetti a vite Con  
interblocco meccanico



Certificati

| TECHDATA                     |                       | NORME E LEGGI                     |   |
|------------------------------|-----------------------|-----------------------------------|---|
| Tipologia prodotto           | PRESA INTERBLOCCATA   | EN 60309-1 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Serie commerciale            | Serie OMNIA           | EN 60309-2 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Descrizione sintetica        | PRESA INTERBLOCCATA   |                                   |   |
| Tipo installazione           | PARETE                |                                   |   |
| Corrente nominale            | 16A                   | EN 60309-1/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Poli                         | 3P+N+T                | EN 60309-2/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Riferimento Orario           | 4h                    |                                   |   |
| Tensione nominale (range)    | 50-200V               | EN 60309-4 (2007)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock   |
| Tensione nominale            | 100-130V              |                                   |   |
| Frequenza d'impiego          | 60Hz                  | EN 60309-1/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Frequenza d'impiego          | 50Hz                  | EN 60309-2/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Colore                       | GIALLO                |                                   |   |
| Materiale                    | TERMOPLASTICO         |                                   |   |
| Grado di protezione generico | Stagno all'immersione | EN 60309-4/A1 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock   |
| Grado di protezione IP       | IP66/IP67             |                                   |   |
| Grado di protezione IK       | IK08                  | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive   |
| Morsetti                     | Morsetti a vite       |                                   |   |
| Materiale di contatto        | CuZn (ottone)         |                                   |   |

|         |                           |
|---------|---------------------------|
| Flangia | 136X125MM_PAR             |
| Opzioni | Con interblocco meccanico |
| Note    | CON BASE PORTAFUSIBILI    |