

Article

243.3293.K
 APPLIANCE INLET 2P+E IP44 32A 6h

Picture**Master data**

Minimum order	10 NR
Net Weight	0.162 KG
EAN code	8001636222264
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	OPTIMA Series
Synthetical description	FLUSH MOUNTING APPLIANCE INLET
Rated current	32A
Poles	2P+E
Hour position	6h
Rated voltage	200-250V
Working frequency	50Hz
Working frequency	60Hz
Colour	BLUE
Protection degree IP	IP44/IP54
Types of available outlets	STRAIGHT
Terminals	Screw terminals
Flange	75X75MM

Approvals and Certifications

UE
 Declaration of conformity



EAC
 Eurasian Conformity

Standards and Laws

EN 60309-1 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations

Packaging**Annexed**

Description	Carton
Quantity	50
EAN code	8001636671475
Gross weight	9.45 KG
Volume	46878.5 CCM
Dimensions	305x580x265 (MM)
Description	Box
Quantity	10
EAN code	8001636671468
Gross weight	1.89 KG
Volume	7128 CCM
Dimensions	220x270x120 (MM)



Technical drawing [DWG]

.dwg



Technical drawing [PDF]

.pdf



Technical drawing [STP]

.stp

Note:

Black-coloured

