

Article**248.1697RV**

OPTIMA REVERSE INLET 3P+N+E 16A IP66/67

Picture**Master data**

Minimum order	10 NR
Net Weight	0.171 KG
EAN code	8001636234649
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	OPTIMA-REVERSE Series
Synthetical description	FLUSH MOUNTING APPLIANCE INLET
Rated current	16A
Poles	3P+N+E
Hour position	6h
Rated voltage	346-415V
Working frequency	50Hz
Working frequency	60Hz
Colour	RED
Protection degree IP	IP66/IP67/IP69
Types of available outlets	STRAIGHT
Terminals	Screw terminals
Flange	75X75MM

Approvals and Certifications

UE
Declaration of conformity



EAC
Eurasian Conformity

Standards and Laws

EN 60309-1 (1999)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2 (1999)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A1 (2007)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 1:
 General requirements



EN 60309-2/A1 (2007)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 2:
 Dimensional interchangeability requirements
 for pin and contact-tube accessories of
 harmonized configurations

Packaging

Description	Carton
Quantity	50
EAN code	8001636686387
Gross weight	9.95 KG
Volume	46878.5 CCM
Dimensions	305x580x265 (MM)
Description	Box
Quantity	10
EAN code	8001636686370
Gross weight	1.99 KG
Volume	7128 CCM
Dimensions	220x270x120 (MM)

Annexed



Instruction manual



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]

Note:

> Phase inverter



> Operating principle of the phase inverter



Articoli Collegati:

	570.90165	PLUG CAP 3P+N+E 16A 20A GREY
--	-----------	------------------------------