

Article**505.16864**

INTERLOCKED SOCKET 3P+E IP67 16A 3h

Picture**Master data**

Minimum order	1 NR
Net Weight	0.627 KG
EAN code	8001636050096
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	OMNIA Series
Synthetical description	INTERLOCKED SOCKET
Rated current	16A
Poles	3P+E
Hour position	3h
Rated voltage	380V 50Hz / 440V 60Hz
Working frequency	50Hz
Working frequency	60Hz
Colour	RED
Protection degree IP	IP66/IP67
Flange	136X125MM_PAR

Approvals and Certifications

UE
Declaration of conformity



I.M.Q. - ENEC 03
European Norms Electrical Certification



EAC
Eurasian Conformity

Standards and Laws

EN 60309-1 (1999)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2 (1999)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A1 (2007)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A1 (2007)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-4 (2007)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock



EN 60309-1/A2 (2012)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A2 (2012)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations

Packaging

Description	Carton
Quantity	6
EAN code	8001636921433
Gross weight	4.098 KG
Volume	17812.5 CCM
Dimensions	150x475x250 (MM)

Annexed



Instruction manual



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]



Note:



Blank side with drilling point mark



Supplied with stainless steel fixing screws.



Note: in case of mounting with ADVANCE2 System, use METRIC drilling point mark.

