

Article**505.2421**

INTERLOCKED SOCKET 2P IP67 16A 12h

Picture**Master data**

Minimum order	6 NR
Net Weight	0.639 KG
EAN code	8001636073989
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	OMNIA Series
Synthetical description	INTERLOCKED SOCKET
Rated current	16A
Poles	2P
Hour position	12h
Rated voltage	40-50V
Working frequency	50Hz
Working frequency	60Hz
Colour	WHITE
Protection degree IP	IP66/IP67
Flange	136X125MM_PAR

Approvals and Certifications

I.M.Q.
Istituto Italiano del Marchio di Qualità



EAC
Eurasian Conformity

Standards and Laws

EN 60309-1 (1999)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2 (1999)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A1 (2007)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A1 (2007)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 2:
 Dimensional interchangeability requirements
 for pin and contact-tube accessories of
 harmonized configurations

Packaging

Description	Carton
Quantity	6
EAN code	8001636884998
Gross weight	4.464 KG
Volume	18427.5 CCM
Dimensions	315x390x150 (MM)

Annexed



Instruction manual



Instruction manual



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]



Note:

> The versions without transformer are particularly suitable for installations with centralised extra-low voltage transformer.



> Blank side with drilling point mark



> Note: in case of mounting with ADVANCE2 System, use METRIC drilling point mark.



> When plug is inserted a micro-switch is activated and closes the circuit



> Flange 136x125mm

