WebService:

09/02/2019

Article

522.1651
SOCKET OUTLET 3P+E IP44 16A 4h 100-130V

Picture

Master data

Minimum order	10 NR
Net Weight	0.208 KG
EAN code	8001636072630
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	OPTIMA Series
Synthetical description	SURFACE MOUNTING SOCKET
Rated current	16A
Poles	3P+E
Hour position	4h
Rated voltage	100-130V
Working frequency	50Hz
Working frequency	60Hz
Colour	YELLOW
Protection degree IP	IP44/IP54
Types of available outlets	STRAIGHT
Terminals	Screw terminals
Cable outlet	DRILLING POINT MARK

Approvals and Certifications

UE
Declaration of conformity

I.M.Q. - ENEC 03
European Norms Electrical Certification

EAC
Eurasian Conformity

Standards and Laws

EN 60309-1 (1999)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements

EN 60309-2 (1999)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations

EN 60309-1/A1 (2007)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements

EN 60309-2/A1 (2007)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations

EN 60309-1/A2 (2012)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements

EN 60309-2/A2 (2012)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations

Packaging

Description	Carton
Quantity	50
EAN code	8001636887531
Gross weight	12.15 KG
Volume	66990 CCM
Dimensions	385x580x300 (MM)
Description	Box
Quantity	10
EAN code	8001636887548
Gross weight	2.43 KG
Volume	9450.54 CCM
Dimensions	258x333x110 (MM)

Annexed

Technical drawing [DWG]

Technical drawing [PDF]

Technical drawing [STP]

Note:

Blank side with drilling point mark

Rubber cable sleeve included