

Article**527.3258**

SOCKET OUTLET 2P+E IP67 32A 9h 380-415V

Picture**Master data**

Minimum order	10 NR
Net Weight	0.368 KG
EAN code	8001636073736
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	OPTIMA Series
Synthetical description	SURFACE MOUNTING SOCKET
Rated current	32A
Poles	2P+E
Hour position	9h
Rated voltage	380-415V
Working frequency	50Hz
Working frequency	60Hz
Colour	RED
Protection degree IP	IP66/IP67/IP69
Types of available outlets	STRAIGHT
Terminals	Screw terminals
Cable outlet	DRILLING POINT MARK

Approvals and Certifications
 UE
 Declaration of conformity

 I.M.Q. - ENEC 03
 European Norms Electrical Certification

 EAC
 Eurasian Conformity
Standards and Laws
 EN 60309-1 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements

 EN 60309-2 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Packaging**Annexed**

Description	Carton
Quantity	40
EAN code	8001636885339
Gross weight	16.92 KG
Volume	109200 CCM
Dimensions	390x560x500 (MM)

Description	Box
Quantity	10
EAN code	8001636885346
Gross weight	4.23 KG
Volume	22015.798 CCM
Dimensions	268x343x239.5 (MM)



Technical drawing [DWG]

.dwg



Technical drawing [PDF]

.pdf



Technical drawing [STP]

.stp

Note:

Blank side with drilling point mark

