

Article**561.32832**

INTERLOCKED SOCKET 2P+E IP67 32A 2h >50V

Picture**Master data**

Minimum order	1 NR
Net Weight	0 KG
EAN code	8001636156187
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	ADVANCE 2 Series
Synthetical description	INTERLOCKED SOCKET
Rated current	32A
Poles	2P+E
Hour position	2h
Rated voltage	>50V
Working frequency	>300-500Hz
Colour	GREEN
Protection degree IP	IP66/IP67
Flange	106X240MM
Cable outlet	M25X1,5

Approvals and Certifications

UE
Declaration of conformity



I.M.Q. - ENEC 03
European Norms Electrical Certification



EAC
Eurasian Conformity

Standards and Laws

EN 60309-1 (1999)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2 (1999)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A1 (2007)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A1 (2007)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-4 (2007)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock



EN 60309-1/A2 (2012)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A2 (2012)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-4/A1 (2012)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock

Packaging

Description	Carton
Quantity	12
EAN code	8001636589497
Gross weight	0 KG
Volume	0
Dimensions	0x0x0 ()
Description	Box
Quantity	1
EAN code	8001636589480
Gross weight	0 KG
Volume	0
Dimensions	0x0x0 ()

Annexed



Technical drawing [DWG]

.dwg



Technical drawing [PDF]

.pdf



Technical drawing [STP]

.stp

Note:

- > Open threaded cable entry 
- > Cable gland included 
- > Threaded cap/cable sleeve included 
- > Supplied with stainless steel fixing screws. 
- > The maximum amount of current available, taking into account the maximum overheating temperature allowed by the relevant standards, must be downgraded with respect to the nominal current by 25% for products with frequencies ranging above 100 Hz; contact Scame Technical Service for further information. 

Articoli Collegati:

	576.4300	MODULAR BASE ADVANCE 2
--	----------	------------------------