

Article**610.3646**

PHASE SEQUENCE ADAPTOR 3P+E 16A 380/415V

Picture**Master data**

Minimum order	10 NR
Net Weight	0.223 KG
EAN code	8001636015606
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	ADAPTO Series
Synthetical description	ONE-WAY ADAPTOR
Protection degree IP	IP44
Inlet supply unit	Plug IEC 309 3P+E 16A
Rated current	16A
Poles	3P+E
Rated voltage	400V
No. of sockets 3P +E 16A	1

Approvals and Certifications

UE
Declaration of conformity



EAC
Eurasian Conformity

Standards and Laws

IEC 60309-1 (1999)
[International Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



IEC 60309-2 (1999)
[International Standard] Plugs, socket-outlets and couplers for industrial purposes. Part: 2: Dimensional interchangeability requirements for pin and contact-tube accessories

Packaging

Description	Carton
Quantity	50
EAN code	8001636879468
Gross weight	12.5 KG
Volume	66990 CCM

Annexed

Dimensions	385x580x300 (MM)
Description	Box
Quantity	10
EAN code	8001636984421
Gross weight	2.5 KG
Volume	9680 CCM
Dimensions	220x275x160 (MM)

Note:

- > Specially useful for temporary connection to the three-phase power supply of machines such as concrete mixers, small cranes, sanders, drills, circular saws, etc.
- > For temporary use only
- > This device reverses the sequence of phases between the power supply and the rotating machine. It must be plugged in between the rotating machine plug and the power supply socket.

