

Article

625.3506-060
 3-WAY ADAPTOR ELEV.INST. IP66

Picture**Master data**

Minimum order	1 NR
Net Weight	2.24 KG
EAN code	8001636042640
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	ADAPTO Series
Synthetical description	MULTI-WAY ADAPTOR
Protection degree IP	IP66
Inlet supply unit	Supply by terminal block
No. of available outlets	3
No. of sockets 2P +E 16A	1
No. of sockets 3P +E 16A	2
In disp. ing/tipo apparecchio	RCBO 4P 16A 0,03A
Max power	9 KW

Approvals and Certifications

UE
 Declaration of conformity



EAC
 Eurasian Conformity

Standards and Laws

IEC/TS 61439-7 (2014-02)
 [International Standard] Low-voltage switchgear and controlgear assemblies - Part 7: Assemblies for specific applications such as: marinas, camping sites, market squares, electric vehicles charging stations.

Packaging

Description	Box
Quantity	1
EAN code	8001636931289
Gross weight	2.381 KG

Annexed

Wiring diagram


Volume	9680 CCM
Dimensions	220x275x160 (MM)

Note:

> Tubular stand to be ordered separately



> Equipped with PG21 cable gland, cable clamp and terminal block.

**Articoli Collegati:**

692.4340

TUBULAR STAND FOR ADAPTORS

Technical Details

3P+N+E	Poles
ADAPTO Series	Commercial series
Stationary distrib.assemblies	Typology
16A	Rated current
Terminal block 16mm ²	Inlet supply unit
AC	Type of current
IP66	Protection degree
IEC/TS 61439-7 (2014-02)	Reference standard
Not applicable	Emergency push button
RCBO	RCD protection
RCBO 4P 16A 0,03A	Device supply unit
9 KW	Max power
ON TURRET	Mounting version
400V	Rated voltage
On two-fronts units	Version

Wiring diagram