

Article

630.3006-060
 PORTABLE DISTRIBUTION ASSEMBLY BLOCK3

Picture**Master data**

Minimum order	1 NR
Net Weight	3.059 KG
EAN code	8001636029221
Harmonized System Code (HSCode)	85371098

TechData

Commercial series	BLOCK Series
Synthetical description	DISTRIBUTION ASSEMBLY (ACS)
Protection degree IP	IP44
Inlet supply unit	Plug
No. of available outlets	3
No. of sockets 2P +E 16A	1
No. of sockets 3P +E 16A	2
In disp. ing/tipo apparecchio	RCBO 4P 16A 0,03A
Max power	9 KW

Approvals and Certifications

UE
 Declaration of conformity

Standards and Laws

EN 61439-4 (2013-03)
 [European Standard] Low-voltage switchgear and controlgear assemblies - Part 4: Particular requirements for assemblies for construction sites (ACS)

Packaging

Description	Carton
Quantity	1
EAN code	8001636930817
Gross weight	3.544 KG
Volume	20527.5 CCM
Dimensions	255x460x175 (MM)

Annexed

Wiring diagram

Note:

Plug IEC309 16A 3P+N+E



1,5m rubber cable H07RN-F

**Technical Details**

3P+N+E	Poles
BLOCK Series	Commercial series
6h	Hour position
Portable distribut. assemblies	Typology
16A	Rated current
Plug IEC 309 3P+N+E 16A	Inlet supply unit
AC	Type of current
IP44	Protection degree
EN 61439-4 (2013-03)	Reference standard
No	Emergency push button
RCBO	RCD protection
RCBO 4P 16A 0,03A	Device supply unit
9 KW	Max power
H07RN-F	Cable
1,5m	Cable length
400V	Rated voltage

Wiring diagram