

**Article****630.3506-055**

DISTRIBUTION ASSEMBLY (ACS) IP66 16A

**Picture****Master data**

|                                 |               |
|---------------------------------|---------------|
| Minimum order                   | 1 NR          |
| Net Weight                      | 2.815 KG      |
| EAN code                        | 8001636248349 |
| Harmonized System Code (HSCode) | 85371098      |

**TechData**

|                               |                             |
|-------------------------------|-----------------------------|
| Commercial series             | BLOCK Series                |
| Synthetical description       | DISTRIBUTION ASSEMBLY (ACS) |
| Protection degree IP          | IP66                        |
| Inlet supply unit             | Plug                        |
| No. of available outlets      | 3                           |
| No. sockets 2P+E 16A IT std.  | 3                           |
| In disp. ing/tipo apparecchio | MCB 2P 16A                  |
| In disp. ing/tipo apparecchio | RCD 2P 25A 0,03A            |
| Max power                     | 3 KW                        |

**Approvals and Certifications**
 UE  
 Declaration of conformity
**Standards and Laws**
 EN 61439-4 (2013-03)  
 [European Standard] Low-voltage switchgear and controlgear assemblies - Part 4: Particular requirements for assemblies for construction sites (ACS)
**Packaging**

|              |                  |
|--------------|------------------|
| Description  | Carton           |
| Quantity     | 1                |
| EAN code     | 8001636696577    |
| Gross weight | 3.3 KG           |
| Volume       | 20527.5 CCM      |
| Dimensions   | 255x460x175 (MM) |

**Annexed**

Wiring diagram

**Note:**

1,5m rubber cable H07RN-F



Plug IEC309 16A 2P+E

**Technical Details**

|                                |                       |
|--------------------------------|-----------------------|
| 2P+E                           | Poles                 |
| BLOCK Series                   | Commercial series     |
| 6h                             | Hour position         |
| Portable distribut. assemblies | Typology              |
| 16A                            | Rated current         |
| Plug IEC 309 2P+E 16A          | Inlet supply unit     |
| AC                             | Type of current       |
| IP66                           | Protection degree     |
| EN 61439-4 (2013-03)           | Reference standard    |
| No                             | Emergency push button |
| Main switch with RCD           | RCD protection        |
| MCB 2P 16A                     | Device supply unit    |
| RCD 2P 25A 0,03A               | Device supply unit    |
| 3 KW                           | Max power             |
| 1,5m                           | Cable length          |
| 230V                           | Rated voltage         |
| With protection appliance      | Version               |