

Article

630.4006-710
 DISTRIBUTION ASSEMBLY (ACS)

Picture**Master data**

Minimum order	1 NR
Net Weight	5.46 KG
EAN code	8001636185149
Harmonized System Code (HSCode)	85371098

TechData

Commercial series	BLOCK Series
Synthetical description	DISTRIBUTION ASSEMBLY (ACS)
Protection degree IP	IP44
Inlet supply unit	Plug
No. of available outlets	3
No. of sockets 2P +E 16A	1
No. of sockets 3P +E 32A	1
No. of sockets 3P +N+E 32A	1
In disp. ing/tipo apparecchio	MCB 4P 32A
In disp. ing/tipo apparecchio	RCD 4P 40A 0,03A
Max power	18 KW
No. MCB 1P+N 16A	1

Approvals and Certifications

UE
 Declaration of conformity

Standards and Laws

EN 61439-4 (2013-03)
 [European Standard] Low-voltage switchgear and controlgear assemblies - Part 4: Particular requirements for assemblies for construction sites (ACS)

Packaging

Description	Carton
-------------	--------

Annexed

Quantity	1
EAN code	8001636639406
Gross weight	6.02 KG
Volume	25501.875 CCM
Dimensions	335x435x175 (MM)



Wiring diagram

Note:

> Plug IEC309 32A 3P+N+E



> 4m rubber cable H07RN-F

**Articoli Collegati:**

	654.0600	BLOCK 4 DISTRIBUTION ASSEMBLY STAND
---	----------	-------------------------------------

Technical Details

3P+N+E	Poles
BLOCK Series	Commercial series
6h	Hour position
Portable distribut. assemblies	Typology
32A	Rated current
Plug IEC 309 3P+N+E 32A	Inlet supply unit
AC	Type of current
IP44	Protection degree
EN 61439-4 (2013-03)	Reference standard
No	Emergency push button
Main switch with RCD	RCD protection
MCB 4P 32A	Device supply unit
RCD 4P 40A 0,03A	Device supply unit
18 KW	Max power
H07RN-F	Cable
4m	Cable length
400V	Rated voltage