

Article**630.4506-473**

PORTABLE DISTRIBUTION ASSEMBLY BLOCK4

Picture**Master data**

Minimum order	1 NR
Net Weight	4.503 KG
EAN code	8001636113142
Harmonized System Code (HSCode)	85371098

TechData

Commercial series	BLOCK Series
Synthetical description	DISTRIBUTION ASSEMBLY (ACS)
Protection degree IP	IP66
Inlet supply unit	Plug
No. of available outlets	4
No. of sockets 2P +E 16A	4
In disp. ing/tipo apparecchio	MCB 4P 16A
In disp. ing/tipo apparecchio	RCD 4P 25A 0,03A
Max power	9 KW

Approvals and Certifications
 UE
 Declaration of conformity
Standards and Laws
 EN 61439-4 (2013-03)
 [European Standard] Low-voltage switchgear and controlgear assemblies - Part 4: Particular requirements for assemblies for construction sites (ACS)
Packaging

Description	Carton
Quantity	1
EAN code	8001636628936
Gross weight	5.06 KG
Volume	25501.875 CCM
Dimensions	335x435x175 (MM)

Annexed

Wiring diagram

Note:

Plug IEC309 16A 3P+N+E



4m rubber cable H07RN-F

**Articoli Collegati:**

654.0600

BLOCK 4 DISTRIBUTION ASSEMBLY STAND

Technical Details

3P+N+E	Poles
BLOCK Series	Commercial series
6h	Hour position
Portable distribut. assemblies	Typology
16A	Rated current
Plug IEC 309 3P+N+E 16A	Inlet supply unit
AC	Type of current
IP66	Protection degree
EN 61439-4 (2013-03)	Reference standard
No	Emergency push button
Main switch with RCD	RCD protection
MCB 4P 16A	Device supply unit
RCD 4P 25A 0,03A	Device supply unit
9 KW	Max power
H07RN-F	Cable
4m	Cable length
400V	Rated voltage