

**Article****632.3000-395**

SURF. MOUNT.DISTRIBUTION ASSEMBLY BLOCK3

**Picture****Master data**

|                                 |               |
|---------------------------------|---------------|
| Minimum order                   | 1 NR          |
| Net Weight                      | 1.726 KG      |
| EAN code                        | 8001636065441 |
| Harmonized System Code (HSCode) | 85371098      |

**TechData**

|                               |                              |
|-------------------------------|------------------------------|
| Commercial series             | BLOCK Series                 |
| Synthetical description       | DISTRIBUTION ASSEMBLY        |
| Protection degree IP          | IP44                         |
| Inlet supply unit             | Direct supply to main switch |
| No. of available outlets      | 3                            |
| No. p.m. socket 2P +E 16A P40 | 2                            |
| No. of sockets 3P +E 16A      | 1                            |
| In disp. ing/tipo apparecchio | MCB 4P 16A                   |
| Max power                     | 9 KW                         |

**Approvals and Certifications**
 UE  
 Declaration of conformity
**Standards and Laws**
 EN 61439-3 (2012-04)  
 [European Standard] Low-voltage switchgear and controlgear assemblies - Part 3: Distribution boards intended to be operated by ordinary persons (DBO)
**Packaging**

|              |                  |
|--------------|------------------|
| Description  | Carton           |
| Quantity     | 1                |
| EAN code     | 8001636900643    |
| Gross weight | 1.98 KG          |
| Volume       | 12477.5 CCM      |
| Dimensions   | 155x460x175 (MM) |

**Annexed**

Wiring diagram

|  |  |
|--|--|
|  |  |
|--|--|

### Technical Details

|                               |                       |
|-------------------------------|-----------------------|
| 3P+N+E                        | Poles                 |
| BLOCK Series                  | Commercial series     |
| Stationary distrib.assemblies | Typology              |
| 16A                           | Rated current         |
| Direct supply to main switch  | Inlet supply unit     |
| AC                            | Type of current       |
| IP44                          | Protection degree     |
| EN 61439-3 (2012-04)          | Reference standard    |
| No                            | Emergency push button |
| Not applicable                | RCD protection        |
| MCB 4P 16A                    | Device supply unit    |
| 9 KW                          | Max power             |
| SURFACE MOUNTING              | Mounting version      |
| 400V                          | Rated voltage         |
| Without protection appliance  | Version               |