

**Article****632.3520-000**

BLOCK 3 DISTRIBUTION BOARD WITH CUTOUTS

**Picture****Master data**

|                                 |               |
|---------------------------------|---------------|
| Minimum order                   | 1 NR          |
| Net Weight                      | 1.098 KG      |
| EAN code                        | 8001636204277 |
| Harmonized System Code (HSCode) | 85381000      |

**TechData**

|                         |                   |
|-------------------------|-------------------|
| Commercial series       | BLOCK Series      |
| Synthetical description | MODULAR ENCLOSURE |
| Mounting version        | SURFACE MOUNTING  |
| Protection degree IP    | IP66              |
| Protection degree IK    | IK08              |
| Dimensions              | 136x440x105mm     |
| Dissipable power        | 9W                |

**Approvals and Certifications**

UE  
Declaration of conformity



I.M.Q.  
Istituto Italiano del Marchio di Qualità

**Standards and Laws**

EN 60670-1 (2005)  
[European Standard] Boxes and enclosures for electrical accessories for household and similar fixed electrical installations. General requirements



EN 60670-24 (2013)  
[European Standard] Boxes and enclosures for electrical accessories for household and similar fixed electrical installations - Part 24: Particular requirements for enclosures for housing protective devices and other power dissipating electrical equipment

**Packaging**

|              |               |
|--------------|---------------|
| Description  | Carton        |
| Quantity     | 4             |
| EAN code     | 8001636753546 |
| Gross weight | 5.012 KG      |

**Annexed**

Instruction manual

|            |                  |
|------------|------------------|
| Volume     | 36800 CCM        |
| Dimensions | 320x460x250 (MM) |
|            |                  |



Technical drawing [DWG]

.dwg



Technical drawing [PDF]




.pdf



Technical drawing [STP]

.stp

### Note:

- > (\*) Cut-outs suitable for 32A socket outlets with 84x106 mm flange 
- > 70x87mm cut-outs 
- > Power dissipation calculated in conformity with CEI 23-49 italian standards 
- > 50x60 mm cut-outs 