

Article

656.5124-006
 DISTRIBUTION ASSEMBLY (ACS)

Picture**Master data**

Minimum order	1 NR
Net Weight	10.25 KG
EAN code	8001636195988
Harmonized System Code (HSCode)	85371098

TechData

Commercial series	MBOX2 Series
Synthetical description	DISTRIBUTION ASSEMBLY (ACS)
Protection degree IP	IP66
Inlet supply unit	Plug
No. of available outlets	4
No. of sockets 2P +E 16A	2
No. of sockets 3P +E 16A	1
No. of sockets 3P +E 32A	1
In disp. ing/tipo apparecchio	MCB 4P 32A
In disp. ing/tipo apparecchio	RCD 4P 40A 0,03A
Max power	18 KW

Approvals and Certifications

UE
 Declaration of conformity



I.M.Q.
 Istituto Italiano del Marchio di Qualità

Packaging

Description	Carton
-------------	--------

Standards and Laws

EN 61439-4 (2013-03)
 [European Standard] Low-voltage
 switchgear and controlgear assemblies -
 Part 4: Particular requirements for
 assemblies for construction sites (ACS)

Annexed

Quantity	1
EAN code	
Gross weight	11.15 KG
Volume	62903.75 CCM
Dimensions	350x455x395 (MM)



Wiring diagram

Note:
 > Plug IEC309 32A 3P+N+E
 

 > 2m rubber cable H07RN-F
 
Articoli Collegati:

	656.0120	STAND KIT MBOX2
---	----------	-----------------

Technical Details

3P+N+E	Poles
MBOX2 Series	Commercial series
6h	Hour position
Portable distribut. assemblies	Typology
23A	Rated current
Plug IEC 309 3P+N+E 32A	Inlet supply unit
AC	Type of current
IP66	Protection degree
EN 61439-4 (2013-03)	Reference standard
No	Emergency push button
Main switch with RCD	RCD protection
MCB 4P 32A	Device supply unit
RCD 4P 40A 0,03A	Device supply unit
18 KW	Max power
400V	Rated voltage
Sockets with fuses	Version

Wiring diagram