

Article**656.7024-273**

MBOX2 W/ TERM.STRIP SOCKET WITHOUT FUSES

Picture**Master data**

Minimum order	1 NR
Net Weight	9.05 KG
EAN code	8001636196459
Harmonized System Code (HSCode)	85371098

TechData

Commercial series	MBOX2 Series
Synthetical description	DISTRIBUTION ASSEMBLY (ACS)
Protection degree IP	IP66
Inlet supply unit	Supply by terminal block
No. of available outlets	4
No. of sockets 2P +E 16A	2
No. of sockets 3P +N+E 16A	1
No. of sockets 3P +N+E 32A	1
In disp. ing/tipo apparecchio	MCB 4P 32A
In disp. ing/tipo apparecchio	RCD 4P 40A 0,03A
Max power	18 KW
No. MCB 1P 16A	2
No. MCB 3P 16A	1

Approvals and Certifications
 UE
 Declaration of conformity

 I.M.Q.
 Istituto Italiano del Marchio di Qualità
Standards and Laws
 EN 61439-4 (2013-03)
 [European Standard] Low-voltage
 switchgear and controlgear assemblies -
 Part 4: Particular requirements for
 assemblies for construction sites (ACS)

Packaging

Description	Carton
Quantity	1
EAN code	
Gross weight	9.9 KG
Volume	54816.125 CCM
Dimensions	305x455x395 (MM)

Annexed


Wiring diagram



Instruction manual

Articoli Collegati:


656.0120

STAND KIT MBOX2

Technical Details

3P+N+E	Poles
MBOX2 Series	Commercial series
Stationary distrib.assemblies	Typology
23A	Rated current
Terminal block 16mm ²	Inlet supply unit
AC	Type of current
IP66	Protection degree
EN 61439-4 (2013-03)	Reference standard
No	Emergency push button
Main switch with RCD	RCD protection
MCB 4P 32A	Device supply unit
RCD 4P 40A 0,03A	Device supply unit
18 KW	Max power
400V	Rated voltage
Sockets without fuses	Version

Wiring diagram
