

Article**692.4300-305**TWO-FRONT RUBBER UNIT FOR CAMPING
GROUND**Picture****Master data**

Minimum order	1 NR
Net Weight	10.345 KG
EAN code	8001636033723
Harmonized System Code (HSCode)	85371098

TechData

Commercial series	GOMMA Series
Synthetical description	DISTRIBUTION ASSEMBLY
Protection degree IP	IP44
Inlet supply unit	Supply by terminal block
No. of available outlets	6
No. of sockets 2P +E 16A	6
In disp. ing/tipo apparecchio	Not applicable
Max power	2,3 KW
No. MCB 1P+N 2A	6
No. RCD 4P 25A 0,03A	2

Approvals and Certifications
 UE
 Declaration of conformity

 EAC
 Eurasian Conformity
Packaging

Description	Carton
Quantity	1
EAN code	8001636926940

Standards and Laws
 IEC/TS 61439-7 (2014-02)
 [International Standard] Low-voltage
 switchgear and controlgear assemblies -
 Part 7: Assemblies for specific applications
 such as: marinas, camping sites, market
 squares, electric vehicles charging stations.
Annexed

Wiring diagram

Gross weight	10.8 KG
Volume	23625 CCM
Dimensions	225x280x375 (MM)

Technical Details

3P+N+E	Poles
GOMMA Series	Commercial series
Stationary distrib.assemblies	Typology
4A	Rated current
Terminal block 10mm ²	Inlet supply unit
AC	Type of current
IP44	Protection degree
IEC/TS 61439-7 (2014-02)	Reference standard
No	Emergency push button
Group outgoing circuit/ sock.	RCD protection
Not applicable	Device supply unit
2,3 KW	Max power
ON TURRET	Mounting version
400V	Rated voltage
On two-fronts units	Version

Wiring diagram

