

**Article****692.4300-69**TWO-FRONT RUBBER UNIT FOR CAMPING  
GROUND**Picture****Master data**

|                                 |               |
|---------------------------------|---------------|
| Minimum order                   | 1 NR          |
| Net Weight                      | 11.135 KG     |
| EAN code                        | 8001636033730 |
| Harmonized System Code (HSCode) | 85371098      |

**TechData**

|                               |                          |
|-------------------------------|--------------------------|
| Commercial series             | GOMMA Series             |
| Synthetical description       | DISTRIBUTION ASSEMBLY    |
| Protection degree IP          | IP44                     |
| Inlet supply unit             | Supply by terminal block |
| No. of available outlets      | 8                        |
| No. of sockets 2P +E 16A      | 8                        |
| In disp. ing/tipo apparecchio | Not applicable           |
| Max power                     | 4 KW                     |
| No. MCB 1P+N 2A               | 8                        |
| No. RCD 4P 25A 0,03A          | 2                        |

**Approvals and Certifications**
 UE  
 Declaration of conformity

 EAC  
 Eurasian Conformity
**Packaging**

|             |               |
|-------------|---------------|
| Description | Carton        |
| Quantity    | 1             |
| EAN code    | 8001636926933 |

**Standards and Laws**
 IEC/TS 61439-7 (2014-02)  
 [International Standard] Low-voltage  
 switchgear and controlgear assemblies -  
 Part 7: Assemblies for specific applications  
 such as: marinas, camping sites, market  
 squares, electric vehicles charging stations.
**Annexed**

Wiring diagram

|              |                  |
|--------------|------------------|
| Gross weight | 11.745 KG        |
| Volume       | 31416 CCM        |
| Dimensions   | 340x385x240 (MM) |
|              |                  |

### Technical Details

|                                  |                       |
|----------------------------------|-----------------------|
| 3P+N+E                           | Poles                 |
| GOMMA Series                     | Commercial series     |
| Stationary distrib.assemblies    | Typology              |
| 8A                               | Rated current         |
| Terminal block 10mm <sup>2</sup> | Inlet supply unit     |
| AC                               | Type of current       |
| IP44                             | Protection degree     |
| IEC/TS 61439-7 (2014-02)         | Reference standard    |
| No                               | Emergency push button |
| Group outgoing circuit/ sock.    | RCD protection        |
| Not applicable                   | Device supply unit    |
| 4 KW                             | Max power             |
| ON TURRET                        | Mounting version      |
| 400V                             | Rated voltage         |
| On two-fronts units              | Version               |

### Wiring diagram

