Механическая блокировка, тип 32, выкатное исполнение, для IZMX40

Тип	**IZMX-MIL32C-W40**
№ для зак.	**153595**
Каталог №	**IZMX40-MIL32C-W**

Программа поставок

Ассортимент			Дополнительное оснащение
Принадлежности			Выдвижной вариант монтажа
Принадлежности			Механическая блокировка
			Type 32
			для 3 автоматических переключателей: Два нормальных провода подачи питания (A, C) и одно соединение (B). Один или два любых переключателя можно включить одновременно. Дополнительно необходимы три набора кабелей.
Применяемое для			IZMX40... IMX40...
			Тросы Боудена
Метод монтажа			Выдвижной вариант монтажа

Bauartnachweis nach IEC/EN 61439

Технические характеристики для подтверждения типа конструкции			
Мин. рабочая температура		°C	-25
Макс. рабочая температура		°C	70

Технические характеристики согласно ETIM 6.0

Low-voltage industrial components (EG000017) / Mechanic interlock for switch (EC001044)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Mechanic interlock for switch (ecl@ss8.1-27-37-13-03 [AKN341010])

Auxiliary contacts, extendable			No
Number of contacts as normally closed contact			0
Number of contacts as normally open contact			0

© 11/2012 by Eaton Industries GmbH