



**Automatización Eléctrica**

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

## General Information

Extended Product Type:	TF140DU-90
Product ID:	1SAZ431201R1001
EAN:	4013614446818
Catalog Description:	TF140DU-90 Thermal Overload Relay
Long Description:	The TF140DU-90 thermal overload relay is an economic electromechanical protection device for the main circuit. It offers reliable and fast protection for motors in the event of overload or phase failure. The device has trip class 10A. Further features are the temperature compensation, trip contact (NC), signal contact (NO), automatic- or manual reset selectable, trip-free mechanism, STOP- and Test function and a trip indication. The overload relays are connected directly to the block contactors.

## Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Thermal Overload Relays

## Ordering

EAN:	4013614446818
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85364900

## Dimensions

Product Net Width:	89 mm
Product Net Height:	140 mm
Product Net Depth:	126 mm
Product Net Weight:	0.82 kg

## Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	165 mm
Package Level 1 Height:	133 mm
Package Level 1 Length:	151 mm
Package Level 1 Gross Weight:	0.945 kg
Package Level 2 Units:	4 piece
Package Level 2 Width:	280 mm
Package Level 2 Height:	210 mm
Package Level 2 Length:	395 mm
Package Level 2 Gross Weight:	8.786 kg
Package Level 2 EAN:	4013614494352

## Technical

Setting Range:	66 ... 90 A
Rated Operational Voltage:	Auxiliary Circuit 440 V DC Auxiliary Circuit 500 V AC Main Circuit 690 V AC
Rated Operational Current ( $I_e$ ):	90 A
Rated Operational Current AC-3 ( $I_e$ ):	90 A
Rated Frequency (f):	Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC Main Circuit 60 Hz Main Circuit 50 Hz Main Circuit DC
Rated Impulse Withstand Voltage ( $U_{imp}$ ):	Auxiliary Circuit 6 kV Main Circuit 8 kV
Rated Insulation Voltage ( $U_i$ ):	690 V
Number of Poles:	3
Number of Auxiliary Contacts NC:	1
Number of Auxiliary Contacts NO:	1
Number of Protected Poles:	3
Conventional Free-air Thermal Current ( $I_{th}$ ):	Auxiliary Circuit NC 10 A Auxiliary Circuit NO 6 A
Rated Operational Current AC-15 ( $I_e$ ):	(120 V) NC 3 A (120 V) NO 1.5 A (240 V) NC 3 A

	(240 V) NO 1.5 A (400 V) NC 1.9 A (400 V) NO 1 A (440 V) NC 1 A (440 V) NO 1 A (500 V) NC 1 A (500 V) NO 1 A
<b>Rated Operational Current DC-13 (I<sub>e</sub>):</b>	(125 V) NC 0.25 A (125 V) NO 0.25 A (24 V) NC 1.25 A (24 V) NO 1.25 A (250 V) NC 0.12 A (250 V) NO 0.04 A (60 V) NC 0.25 A (60 V) NO 0.25 A
<b>Degree of Protection:</b>	Housing IP20 Main Circuit Terminals IP10
<b>Pollution Degree:</b>	3
<b>Connecting Capacity-Auxiliary Circuit:</b>	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup> Flexible 1/2x 0.75 ... 2.5 mm <sup>2</sup> Rigid 1/2x 0.75 ... 4 mm <sup>2</sup>
<b>Connecting Capacity-Main Circuit:</b>	Flexible with Ferrule 1/2x 16 ... 70 mm <sup>2</sup> Flexible with Insulated Ferrule 1/2x 16 ... 70 mm <sup>2</sup> Flexible 1/2x 16 ... 70 mm <sup>2</sup> Rigid 1/2x 16 ... 70 mm <sup>2</sup>
<b>Tightening Torque:</b>	Auxiliary Circuit 0.8 ... 1.2 N·m Main Circuit 8 ... 10 N·m
<b>Wire Stripping Length:</b>	Auxiliary Circuit 9 mm Main Circuit 25 mm
<b>Recommended Screw Driver:</b>	Auxiliary Circuit Pozidriv 2 Main Circuit Hexagon 4
<b>Mounting Position:</b>	Position 1 to 5
<b>Power Loss:</b>	at Rated Operating Conditions per Pole 2.4 ... 4.4 W
<b>Suitable For:</b>	AF116 AF140
<b>Standards:</b>	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1

## Environmental

<b>Ambient Air Temperature:</b>	Operation -25 ... +55 °C Operation Compensated -25 ... +55 °C Storage -40 ... +70 °C
<b>Ambient Air Temperature Compensation:</b>	Yes
<b>Maximum Operating Altitude Permissible:</b>	2000 m
<b>Resistance to Shock acc. to IEC 60068-2-27:</b>	11 ms Pulse 12g
<b>RoHS Status:</b>	Following EU Directive 2002/95/EC August 18, 2005 and amendment

## Technical UL/CSA

<b>Maximum Operating Voltage UL/CSA:</b>	Main Circuit 600 V AC
<b>Ampere Rating UL/CSA:</b>	90 A
<b>Contact Rating UL/CSA:</b>	(NC:) B600 (NO:) C300
<b>Connecting Capacity Main Circuit UL/CSA:</b>	Flexible 1/2x 6 ... 2/0 AWG Stranded 1/2x 6 ... 2/0 AWG
<b>Connecting Capacity Auxiliary Circuit UL/CSA:</b>	Flexible 1/2x 18 ... 14 AWG Stranded 1/2x 18 ... 14 AWG
<b>Tightening Torque UL/CSA:</b>	Auxiliary Circuit 12 in·lb

## Certificates and Declarations (Document Number)

<b>ABS Certificate:</b>	1SAA941004-0101
<b>BV Certificate:</b>	1SAA941003-0201
<b>CB Certificate:</b>	1SAA941012-2001
<b>CCC Certificate:</b>	1SAA941009-3801
<b>cUL Certificate:</b>	cUL_E48139
<b>Declaration of Conformity - CE:</b>	1SAD938502-0185

<b>DNV Certificate:</b>	1SAA941004-0301
<b>EAC Certificate:</b>	1SAA941002-2701
<b>GOST Certificate:</b>	1SAA941001-2701
<b>LR Certificate:</b>	1SAA941004-0501
<b>RINA Certificate:</b>	RINA_ELE098115XG
<b>RoHS Information:</b>	1SAA941006-4403
<b>UL Certificate:</b>	UL_E48139

**Classifications**

<b>Object Classification Code:</b>	F
<b>eClass:</b>	7.0 27371501
<b>ETIM 4:</b>	EC000106 - Thermal overload relay
<b>ETIM 5:</b>	EC000106 - Thermal overload relay
<b>UNSPSC:</b>	39121521





**Automatización Eléctrica**  
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

Product	Code	Reference	Product link
TF140DU-90 Thermal Overload Relay	1SAZ431201R1001	TF140DU-90	<a href="#">Buy on EAN</a>