



**Automatización Eléctrica**

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

## General Information

Extended Product Type:	CA5-04N
Product ID:	1SBN010040R1204
EAN:	3471522121196
Catalog Description:	CA5-04N Auxiliary Contact Block
Long Description:	CA5-04N Auxiliary Contact Block

## Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Block Contactors Accessories  
 Parts & Services » Drives » Medium Voltage AC Drives » Industrial Drives » ACS1000

## Ordering

EAN:	3471522121196
Minimum Order Quantity:	2 piece
Customs Tariff Number:	85389099

## Dimensions

Product Net Weight:	0.060 kg
---------------------	----------

## Container Information

Package Level 1 Units:	2 piece
Package Level 1 Gross Weight:	0.12 kg
Package Level 1 EAN:	3471522121196
Package Level 2 Units:	120 piece

## Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
--------------	---

## Additional Information

Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20
IIT Publishing Status:	Level 0 - Information enabled
Maximum Electrical Switching Frequency:	1200 cycles per hour
Maximum Mechanical Switching Frequency:	3600 cycles per hour
Mechanical Durability:	N... 10 million
Minimum Switching Capacity:	N 17 / 5 volt per milliamp
Mounting on Contactors:	N, NE
Mounting Position:	Front face
Number of Auxiliary Contacts NC:	4
Power Loss:	at Rated Operating Conditions per Pole 0.1 W
Product Main Type:	Accessories for Block Contactors
Product Name:	Auxiliary Contact Block
Rated Breaking Capacity acc. to IEC 60947-5-1:	10 x Ie AC-15
Rated Frequency (f):	Supply Circuit 50 Hz Supply Circuit 60 Hz
Rated Insulation Voltage (U <sub>i</sub> ):	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V acc. to UL/CSA 600 V
Rated Making Capacity acc. to IEC 60947-5-1:	10 x Ie AC-15
Rated Operational Current AC-15 (I <sub>e</sub> ):	(220 / 240 V) 4 A (24 / 127 V) 6 A (380 / 440 V) 3 A (500 V) 2 A (690 V) 2 A
Rated Operational Current DC-13 (I <sub>e</sub> ):	(125 V) 0.55 / 69 A (24 V) 6 / 144 A (250 V) 0.3 / 75 A (48 V) 2.8 / 134 A (72 V) 1 / 72 A
Rated Operational Voltage:	Auxiliary Circuit 690 V Main Circuit 24 V
Rated Short-time Withstand Current	for 1 s 140.0 A

(l <sub>cw</sub> ):	
Remarks:	100
Technical Information:	CA5-04N (4XNC)
Terminal Type:	Screw Terminals

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SBC100122C0202_Ch04
Declaration of Conformity - CE:	1SBD250801C5000
EAC Certificate:	EAC_RU C-FR ME77 B01048
GOST Certificate:	GOST_POCCFRME77B07174
RINA Certificate:	RINA_ELE128713XG002
RoHS Information:	1SBD350058R1000

Classifications

ETIM 4:	EC002498 - Accessories for low-voltage switch technology
ETIM 5:	EC002498 - Accessories for low-voltage switch technology
Object Classification Code:	K
UNSPSC:	39121500

Where Used (as a spare part for "Products")

1 Products (0 listed / 1 unlisted)		Filter	
Identifier	Description	Qty	Unit Of Measure
ACS 1000	No Description Available	1	piece

Product specific part data

1 Products		Filter	
Product	Category	Drive Part Category	
ACS 1000	ACS1000	Switches, Relays, Contactors	





**Automatización Eléctrica**  
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

Product	Code	Reference	Product link
CA5-04N Auxiliary Contact Block	1SBN010040R1204	CA5-04N	<a href="#">Buy on EAN</a>