



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

| | |
|------------------------|-----------------------------------|
| Extended Product Type: | VE5-1 |
| Product ID: | 1SBN030110R1000 |
| EAN: | 3471522121370 |
| Catalog Description: | VE5-1 Block Contactor Accessories |
| Long Description: | VE5-1 Block Contactor Accessories |

Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Block Contactors Accessories

Ordering

| | |
|-------------------------|---------------|
| EAN: | 3471522121370 |
| Minimum Order Quantity: | 1 piece |
| Customs Tariff Number: | 85389099 |

Dimensions

| | |
|---------------------|----------|
| Product Net Weight: | 0.076 kg |
|---------------------|----------|

Container Information

| | |
|-------------------------------|---------------|
| Package Level 1 Units: | 1 piece |
| Package Level 1 Gross Weight: | 0.076 kg |
| Package Level 1 EAN: | 3471522121370 |
| Package Level 2 Units: | 90 piece |

Environmental

| | |
|--------------|---|
| RoHS Status: | Following EU Directive 2002/95/EC August 18, 2005 and amendment |
|--------------|---|

Additional Information

| | |
|---|--|
| Conventional Free-air Thermal Current (I_{th}): | acc. to IEC 60947-5-1, $q = 40\text{ °C}$ 16.0 A |
| IIT Publishing Status: | Level 0 - Information enabled |
| Mechanical Durability: | 5 million |
| Mounted Auxiliary Contacts: | 0 NO, 2 NC |
| Mounting on Contactors: | A 9 ...A 40, N |
| Mounting Type: | rail or plate not supplied |
| Number of Auxiliary Contacts NC: | 2 |
| Power Loss: | at Rated Operating Conditions per Pole 0.1 W |
| Product Main Type: | Accessories for Block Contactors |
| Product Name: | Block Contactor Accessories |
| Rated Breaking Capacity acc. to IEC 60947-5-1: | 10 x I_e AC-15 |
| Rated Frequency (f): | Supply Circuit 50 Hz Supply Circuit 60 Hz |
| Rated Insulation Voltage (U_i): | acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V acc. to UL/CSA 600 V |
| Rated Making Capacity acc. to IEC 60947-5-1: | 10 x I_e AC-15 |
| Rated Operational Current AC-15 (I_e): | (220 / 240 V) 4 A (24 / 127 V) 6 A (380 / 440 V) 3 A (500 V) 2 A (690 V) 2 A |
| Rated Operational Current DC-13 (I_e): | (125 V) 0.55 A (24 V) 6 A (250 V) 0.3 A (48 V) 2.8 A (72 V) 1 A |
| Rated Operational Voltage: | Auxiliary Circuit 690 V |
| Rated Short-time Withstand Current (I_{cw}): | for 0.1 s 140.0 A for 1 s 100 A |
| Terminal Type: | Screw Terminals |
| Version: | Mechanical/Electrical |

Certificates and Declarations (Document Number)

Data Sheet, Technical Information: 1SBC100122C0202_Ch04

Declaration of Conformity - CE: 1SBD250802C3000

GOST Certificate: GOST_POCCFRME77B07175

RINA Certificate: RINA_ELE128713XG001

RoHS Information: 1SBC101061D0201

Classifications

E-number: 3228825

ETIM 4: EC002498 - Accessories for low-voltage switch technology

ETIM 5: EC002498 - Accessories for low-voltage switch technology

UNSPSC: 39120000





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

| Product | Code | Reference | Product link |
|-----------------------------------|-----------------|------------------|----------------------------|
| VE5-1 Block Contactor Accessories | 1SBN030110R1000 | VE5-1 | Buy on EAN |