



## Automatización Eléctrica Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking <u>HERE</u>

## IPSY1A11



IPSY1A11 1SD/002105D1111				
1SBV002105R1111				
3471522009685				
IPSY1A11 Foot Switch				
IPSY1A11 Foot Switch				
nd Systems » Control Products » Sensors » Limit Switches				
0.171.70000007				
3471522009685				
ty: 1 piece : 85369085				
85369085				
1.100 kg				
1 piece				
290 mm				
165 mm				
160 mm				
1.1 kg 3471522009685				
347 1322009003				
Operation -10 … +70 °C Storage -30 … +80 °C				
Half-sine Pulse for 11 ms, No Change in Contact Position 50 m/s <sup>2</sup>				
$c$ 25g (10 to 500 Hz) no change in position of contacts greater than 100 $\mu s$				
$c$ 25g (10 to 500 Hz) no change in position of contacts greater than 100 $\mu s$				
${f C}$ 25g (10 to 500 Hz) no change in position of contacts greater than 100 $\mu s$				
<ul> <li>25g (10 to 500 Hz) no change in position of contacts greater than 100 µs</li> <li>A600</li> </ul>				
A600 Q600				
. A600				
A600 Q600				
A600 Q600				
<ul> <li>A600 Q600 V0</li> <li>t snap action contacts</li> </ul>				
. A600 Q600 V0 t snap action contacts acc. to IEC 60947-5-1 Min. 0.25 N·m				
<ul> <li>A600 Q600</li> <li>V0</li> <li>t snap action contacts acc. to IEC 60947-5-1 Min. 0.25 N·m Grey</li> </ul>				
<ul> <li>A600 Q600</li> <li>V0</li> <li>t snap action contacts</li> <li>acc. to IEC 60947-5-1 Min. 0.25 N·m Grey</li> <li>1 pre-pressed Pg16 knockout on each side</li> </ul>				
<ul> <li>A600 Q600</li> <li>V0</li> <li>t snap action contacts acc. to IEC 60947-5-1 Min. 0.25 N·m Grey</li> </ul>				
<ul> <li>A600 Q600 V0</li> <li>t snap action contacts</li> <li>acc. to IEC 60947-5-1 Min. 0.25 N·m Grey</li> <li>1 pre-pressed Pg16 knockout on each side</li> <li>according to IEC 68-2-3 and salty mist according to IEC 68-2-11</li> <li>AWG 20 AWG 14 0.5 2.5 mm<sup>2</sup></li> </ul>				
<ul> <li>A600 Q600 V0</li> <li>t snap action contacts</li> <li>acc. to IEC 60947-5-1 Min. 0.25 N·m Grey</li> <li>1 pre-pressed Pg16 knockout on each side</li> <li>according to IEC 68-2-3 and salty mist according to IEC 68-2-11</li> <li>AWG 20 AWG 14 0.5 2.5 mm<sup>2</sup></li> <li>M3.5 (+,-) screw Phillips head n 1 with captive cable gland</li> </ul>				
<ul> <li>A600 Q600 V0</li> <li>t snap action contacts</li> <li>acc. to IEC 60947-5-1 Min. 0.25 N·m Grey</li> <li>1 pre-pressed Pg16 knockout on each side</li> <li>according to IEC 68-2-3 and salty mist according to IEC 68-2-11</li> <li>AWG 20 AWG 14 0.5 2.5 mm<sup>2</sup></li> </ul>				
<ul> <li>A600 Q600 V0</li> <li>t snap action contacts</li> <li>acc. to IEC 60947-5-1 Min. 0.25 N·m Grey</li> <li>1 pre-pressed Pg16 knockout on each side</li> <li>according to IEC 68-2-3 and salty mist according to IEC 68-2-11</li> <li>AWG 20 AWG 14 0.5 2.5 mm<sup>2</sup></li> <li>M3.5 (+,-) screw Phillips head n 1 with captive cable gland</li> </ul>				
<ul> <li>A600 Q600 V0</li> <li>t snap action contacts</li> <li>acc. to IEC 60947-5-1 Min. 0.25 N·m Grey</li> <li>1 pre-pressed Pg16 knockout on each side</li> <li>according to IEC 68-2-3 and salty mist according to IEC 68-2-11</li> <li>AWG 20 AWG 14 0.5 2.5 mm<sup>2</sup></li> <li>M3.5 (+,-) screw Phillips head n<sup>(1)</sup> 1 with captive cable gland</li> <li>Za</li> </ul>				
<ul> <li>A600 Q600 V0</li> <li>t snap action contacts</li> <li>acc. to IEC 60947-5-1 Min. 0.25 N·m Grey</li> <li>1 pre-pressed Pg16 knockout on each side</li> <li>according to IEC 68-2-3 and salty mist according to IEC 68-2-11 AWG 20 AWG 14 0.5 2.5 mm<sup>2</sup></li> <li>M3.5 (+,-) screw Phillips head n 1 with captive cable gland</li> <li>Za</li> <li>acc. to IEC 60947-5-1, q = 40 °C 10.0 A</li> </ul>				
<ul> <li>A600 Q600 V0</li> <li>t snap action contacts</li> <li>acc. to IEC 60947-5-1 Min. 0.25 N·m Grey</li> <li>1 pre-pressed Pg16 knockout on each side</li> <li>according to IEC 68-2-3 and salty mist according to IEC 68-2-11</li> <li>AWG 20 AWG 14 0.5 2.5 mm<sup>2</sup></li> <li>M3.5 (+,-) screw Phillips head n 1 with captive cable gland</li> <li>Za</li> <li>acc. to IEC 60947-5-1, q = 40 °C 10.0 A</li> <li>yellow</li> </ul>				
<ul> <li>A600 Q600 V0</li> <li>t snap action contacts</li> <li>acc. to IEC 60947-5-1 Min. 0.25 N·m Grey</li> <li>1 pre-pressed Pg16 knockout on each side</li> <li>according to IEC 68-2-3 and salty mist according to IEC 68-2-11</li> <li>AWG 20 AWG 14 0.5 2.5 mm<sup>2</sup></li> <li>M3.5 (+,-) screw Phillips head n 1 with captive cable gland</li> <li>Za</li> <li>acc. to IEC 60947-5-1, q = 40 °C 10.0 A</li> <li>yellow</li> <li>acc. to IEC 60529 IP65 Double insulation - Class II</li> </ul>				
<ul> <li>A600 Q600 V0</li> <li>t snap action contacts</li> <li>acc. to IEC 60947-5-1 Min. 0.25 N·m Grey</li> <li>1 pre-pressed Pg16 knockout on each side</li> <li>according to IEC 68-2-3 and salty mist according to IEC 68-2-11</li> <li>AWG 20 AWG 14 0.5 2.5 mm<sup>2</sup></li> <li>M3.5 (+,-) screw Phillips head n 1 with captive cable gland</li> <li>Za</li> <li>acc. to IEC 60947-5-1, q = 40 °C 10.0 A</li> <li>yellow</li> <li>acc. to IEC 60529 IP65</li> <li>Double insulation - Class II</li> <li>Level 0 - Information enabled</li> </ul>				
<ul> <li>A600 Q600 V0</li> <li>t snap action contacts</li> <li>acc. to IEC 60947-5-1 Min. 0.25 N·m Grey</li> <li>1 pre-pressed Pg16 knockout on each side</li> <li>according to IEC 68-2-3 and salty mist according to IEC 68-2-11</li> <li>AWG 20 AWG 14 0.5 2.5 mm<sup>2</sup></li> <li>M3.5 (+,-) screw Phillips head n 1 with captive cable gland</li> <li>Za</li> <li>acc. to IEC 60947-5-1, q = 40 °C 10.0 A</li> <li>yellow</li> <li>acc. to IEC 60529 IP65</li> <li>Double insulation - Class II</li> <li>Level 0 - Information enabled</li> <li>.5</li> </ul>				
<ul> <li>A600 Q600 V0</li> <li>t snap action contacts</li> <li>acc. to IEC 60947-5-1 Min. 0.25 N·m Grey</li> <li>1 pre-pressed Pg16 knockout on each side</li> <li>according to IEC 68-2-3 and salty mist according to IEC 68-2-11</li> <li>AWG 20 AWG 14 0.5 2.5 mm<sup>2</sup></li> <li>M3.5 (+,-) screw Phillips head n 1 with captive cable gland</li> <li>Za</li> <li>acc. to IEC 60947-5-1, q = 40 °C 10.0 A</li> <li>yellow</li> <li>acc. to IEC 60529 IP65</li> <li>Double insulation - Class II</li> <li>Level 0 - Information enabled</li> </ul>				

Number of Auxiliary Contacts NC:	1			
Number of Auxiliary Contacts NO:	1			
Operating Angle of the Foot Switch Pedal:	15°			
Operating Format:	free movement			
Positive Opening Operation of NC Contact(s):	Yes			
Product Main Type:	Foot Switches			
Product Name:	Foot Switch			
Rated Frequency (f):	Supply Circuit 50 Hz Supply Circuit 60 Hz			
Rated Impulse Withstand Voltage (U <sub>imp</sub> ):	6 kV			
Rated Insulation Voltage (Ui):	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V acc. to UL/CSA 600 V			
Rated Operational Current AC-15 (I <sub>e</sub> ):	(130 V) 5.5 A (230 V) 3.1 A (240 V) 3 A (24 V) 10 A (400 V) 1.8 A			
Rated Operational Current DC-13 (I <sub>e</sub> ):	(110 V) 0.6 / 66 A (24 V) 2.8 / 67.2 A (250 V) 0.27 / 67.5 A			
Resistance Between Contacts:	25 mΩ			
Standards:	IEC 60947-1, IEC 60947-5-1, EN 60947-1, EN 60947-5-1, UL 508 and CSA C22-2 N°14			
Terminal Marking:	according to EN 50013			

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SBC001699R1002
Declaration of Conformity - CE:	1SBD250882C2000

## Classifications

E-nummer:	3705045
ETIM 4:	EC001829 - Position switch modular
ETIM 5:	EC001829 - Position switch modular
Object Classification Code:	В
UNSPSC:	39121500







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product	Code	Reference	Product link
IPSY1A11 Foot Switch	1SBV002105R1111	IPSY1A11	Buy on EAN