



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking <u>HERE</u>



General Information

IPSG1A22 **Extended Product Type: Product ID:** 1SBV002106R1122 EAN: 3471522009753 **Catalog Description:** IPSG1A22 Foot Switch Long Description: IPSG1A22 Foot Switch

Categories

Products » Low Voltage Products and Systems » Control Products » Sensors » Limit Switches

Ordering

EAN: 3471522009753 **Minimum Order Quantity:** 1 piece **Customs Tariff Number:** 85369085

Dimensions

Product Net Weight: 1.100 kg

Container Information

Package Level 1 Units: 1 piece Package Level 1 Width: 290 mm Package Level 1 Height: 165 mm Package Level 1 Length: 160 mm Package Level 1 Gross Weight: 1.1 kg Package Level 1 EAN: 3471522009753

Environmental

Ambient Air Temperature: Operation -10 ... +70 °C Storage -30 ... +80 °C

Resistance to Shock acc. to IEC Half-sine Pulse for 11 ms, No Change in Contact Position 50 m/s² 60068-2-27:

Resistance to Vibrations acc. to IEC 25g (10 to 500 Hz) no change in position of contacts greater than 100 µs

60068-2-6:

Technical UL/CSA

Pilot Duty of Contact Elements acc. A600 UL508: Q600 Flammability According to UL94: V0

Additional Information

Action Type of the Contact Element snap action contacts

(acc. to IEC 60947-5-1):

acc. to IEC 60947-5-1 Min. 0.25 N·m **Actuation Torque:**

Base Color:

Cable Outlets Per Side: 1 pre-pressed Pg16 knockout on each side

Climatic Withstand: according to IEC 68-2-3 and salty mist according to IEC 68-2-11

Connecting Capacity: AWG 20 ... AWG 14 0.5 ... 2.5 mm²

open position):

Connecting terminals (delivered in M3.5 (+,-) screw Phillips head not with captive cable gland

Contact Element Form (acc. to IEC Za

Conventional Free-air Thermal

60947-5-1):

acc. to IEC 60947-5-1, q = 40 °C 10.0 A

Current (Ith): **Cover Color:** arev

Degree of Protection: acc. to IEC 60529 IP65 Electrical Shock Protection acc. to Double insulation - Class II IEC 536:

IIT Publishing Status: Level 0 - Information enabled

Load Factor: .5 **Mechanical Durability:** 30 million Number and Type of Bottom Cable Pg 16 Cable Gland

Glands:

Number of Auxiliary Contacts NC: 2
Number of Auxiliary Contacts NO: 2
Operating Angle of the Foot Switch 15°

Pedal:

Operating Format: free movement

Positive Opening Operation of NC Yes

Contact(s):

Product Main Type:Foot SwitchesProduct Name:Foot SwitchRated Frequency (f):Supply Circuit 50 Hz
Supply Circuit 60 Hz

Rated Impulse Withstand Voltage 6

(U_{imp}):

6 kV

Rated Insulation Voltage (Ui): acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V

acc. to UL/CSA 600 V

Rated Operational Current AC-15

(l_e):

(130 V) 5.5 A (230 V) 3.1 A (240 V) 3 A (24 V) 10 A (400 V) 1.8 A

Rated Operational Current DC-13

(l_e):

(110 V) 0.6 / 66 A (24 V) 2.8 / 67.2 A (250 V) 0.27 / 67.5 A

Resistance Between Contacts: 25 mΩ

Standards: IEC 60947-5-1, EN 60947-5-1, EN 60947-5-1, UL 508 and CSA C22-2 N°14

Terminal Marking: according to EN 50013

Certificates and Declarations (Document Number)

Data Sheet, Technical Information: 1SBC001699R1002

Declaration of Conformity - CE: 1SBD250882C2000

Classifications

ETIM 4:	EC001829 - Position switch modular	
ETIM 5:	EC001829 - Position switch modular	
UNSPSC:	39121500	







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
IPSG1A22 Foot Switch	1SBV002106R1122	IPSG1A22	Buy on EAN