



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking <u>HERE</u>



General Information

IPSR2D11 **Extended Product Type: Product ID:** 1SBV002208R1411 EAN: 3471522009500 **Catalog Description:** IPSR2D11 Foot Switch Long Description: IPSR2D11 Foot Switch

Categories

Products » Low Voltage Products and Systems » Control Products » Sensors » Limit Switches

Ordering

EAN: 3471522009500 **Minimum Order Quantity:** 1 piece **Customs Tariff Number:** 85369085

Dimensions

Product Net Weight: 1.100 kg

Container Information

Package Level 1 Units: 1 piece Package Level 1 Width: 290 mm 165 mm Package Level 1 Height: Package Level 1 Length: 160 mm Package Level 1 Gross Weight: 1.1 kg Package Level 1 EAN: 3471522009500

Environmental

Ambient Air Temperature: Operation -10 ... +70 °C Storage -30 ... +80 °C

Resistance to Shock acc. to IEC Half-sine Pulse for 11 ms, No Change in Contact Position 50 m/s² 60068-2-27:

Resistance to Vibrations acc. to IEC 25g (10 to 500 Hz) no change in position of contacts greater than 100 µs

60068-2-6:

Technical UL/CSA

Pilot Duty of Contact Elements acc. A600 UL508: Q600 Flammability According to UL94: V0

Additional Information

Action Type of the Contact Element non-overlapping slow action contacts

(acc. to IEC 60947-5-1):

acc. to IEC 60947-5-1 Min. 0.25 N·m **Actuation Torque:**

Base Color: Grey

Cable Outlets Per Side: 1 pre-pressed Pg16 knockout on each side

Climatic Withstand: according to IEC 68-2-3 and salty mist according to IEC 68-2-11

Connecting Capacity: AWG 20 ... AWG 14 0.5 ... 2.5 mm²

open position):

Connecting terminals (delivered in M3.5 (+,-) screw Phillips head not with captive cable gland

Contact Element Form (acc. to IEC Zb

60947-5-1):

Current (Ith):

Conventional Free-air Thermal

acc. to IEC 60947-5-1, q = 40 °C 10.0 A

Cover Color:

acc. to IEC 60529 IP65 Degree of Protection: Electrical Shock Protection acc. to Double insulation - Class II IEC 536:

IIT Publishing Status: Level 0 - Information enabled

Load Factor: .5 **Mechanical Durability:** 30 million Number and Type of Bottom Cable Pg 16 Cable Gland

Glands:

Number of Auxiliary Contacts NC: 1
Number of Auxiliary Contacts NO: 1
Operating Angle of the Foot Switch 15°

Pedal:

Operating Format: locked in neutral position

Positive Opening Operation of NC Ye

Contact(s):

Product Main Type: Foot Switches
Product Name: Foot Switch

Rated Frequency (f): Supply Circuit 50 Hz

Supply Circuit 60 Hz

Rated Impulse Withstand Voltage

(U_{imp}):

6 kV

Rated Insulation Voltage (Ui): acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V

acc. to UL/CSA 600 V

Rated Operational Current AC-15

(l_e):

(130 V) 5.5 A (230 V) 3.1 A (240 V) 3 A (24 V) 10 A (400 V) 1.8 A

Rated Operational Current DC-13

(l_e):

(110 V) 0.6 / 66 A (24 V) 2.8 / 67.2 A (250 V) 0.27 / 67.5 A

Resistance Between Contacts: 25 mg

Standards: IEC 60947-5-1, EN 60947-5-1, EN 60947-5-1, UL 508 and CSA C22-2 N°14

Terminal Marking: according to EN 50013

Certificates and Declarations (Document Number)

Data Sheet, Technical Information: 1SBC001699R1002

Declaration of Conformity - CE: 1SBD250882C2000

Classifications

ETIM 4:	EC001829 - Position switch modular	
ETIM 5:	EC001829 - Position switch modular	
UNSPSC:	39121500	







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
IPSR2D11 Foot Switch	1SBV002208R1411	IPSR2D11	Buy on EAN