



Automatización Eléctrica Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking <u>HERE</u>

LS40P53B11



General Information					
Extended Product Type:	LS40P53B11				
Product ID:	1SBV010553R1211				
EAN:	3471522002051				
Catalog Description:	LS40P53B11 Limit Switch				
Long Description:	LS40P53B11 Limit Switch				
0-1					
Categories	d Customer, N. Canterl Decidente, N. Concerne, N. Lineit Cuitabas				
Products » Low Voltage Products and	d Systems » Control Products » Sensors » Limit Switches				
Ordering					
EAN:	2474522002051				
	3471522002051				
Minimum Order Quantity: Customs Tariff Number:	10 piece				
Customs farm number:	85369085				
Dimensions					
Product Net Width:	40 mm				
Product Net Weight:	0.200 kg				
Troduct Net Weight.	0.200 Ng				
Container Information					
Package Level 1 Units:	1 piece				
Package Level 1 Width:	140 mm				
Package Level 1 Height:	70 mm				
Package Level 1 Length:	45 mm				
Package Level 1 Gross Weight:	0.2 kg				
Package Level 1 EAN:	3471522002051				
Environmental					
Ambient Air Temperature:	Operation -25 +70 °C				
· · · · · · · · · · · · · · · · · · ·	Storage -30 +80 °C				
Resistance to Shock acc. to IEC 60068-2-27:	Half-sine Pulse for 11 ms, No Change in Contact Position 50 m/s ²				
Resistance to Vibrations acc. to IEC 60068-2-6:	25g (10 to 500 Hz) no change in position of contacts greater than 100 μs				
Technical UL/CSA					
Pilot Duty of Contact Elements acc.					
	Q600				
Flammability According to UL94:	V0				
Additional Information					
Action Type of the Contact Element	snap action contacts				
(acc. to IEC 60947-5-1):					
Actuation Speed:	acc. to IEC 60947-5-1 Max. 1.50 m/s				
	acc. to IEC 60947-5-1 Min. 0.00 m/s				
Actuation Torque:	acc. to IEC 60947-5-1 Min. 0.15 N·m				
Actuator Type:	adjustable Ø 22 mm steel ball-bearing roller lever				
Angular Head Adjustment:	adjustable head every 90°				
Angular Lever Adjustment:	9° in 9°				
Climatic Withstand:	according to IEC 68-2-3 and salty mist according to IEC 68-2-11				
Connecting Capacity:	AWG 20 AWG 14 0.5 2.5 mm ²				
Connecting terminals (delivered in open position):	M3.5 (+,-) pozidriv 2 screw with cable clamp				
Consistency (Measured over 1 Million Operations):	0.1 mm				
Contact Element Form (acc. to IEC 60947-5-1):	Zb				
Conventional Free-air Thermal	acc. to IEC 60947-5-1, q = 40 °C 10.0 A				
Current (I _{th}):					
Current (I _{th}): Degree of Protection:	acc. to IEC 60529 IP65				
	acc. to IEC 60529 IP65 Double insulation - Class II				
Degree of Protection:					

IIT Publishing Status:	Level 0 - Information enabled			
Load Factor:	.5			
Maximum Electrical Switching Frequency:	3600 cycles per hour			
Mounting by Screws (not supplied):	2 or 4 x M5 screws			
Mounting Position:	all positions are authorised			
Movement to be Detected:	30° Cam Translation Movement			
Number and Type of Bottom Cable Glands:	Pg 13,5 Cable Gland			
Number of Auxiliary Contacts NC:	1			
Number of Auxiliary Contacts NO:	1			
Positive Opening Operation of NC Contact(s):	No			
Product Main Type:	LS40			
Product Name:	Limit Switch			
Rated Frequency (f):	Supply Circuit 50 Hz Supply Circuit 60 Hz			
Rated Impulse Withstand Voltage (U _{imp}):	6 kV			
Rated Insulation Voltage (Ui):	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V acc. to UL/CSA 600 V			
Rated Operational Current AC-15 (I _e):	(130 V) 5.5 A (230 V) 3.1 A (240 V) 3 A (24 V) 10 A (400 V) 1.8 A			
Rated Operational Current DC-13 (I _e):	(110 V) 0.6 / 66 A (24 V) 2.8 / 67.2 A (250 V) 0.27 / 67.5 A			
Resistance Between Contacts:	25 mΩ			
Standards:	IEC 60947-1, IEC 60947-5-1, EN 60947-1, EN 60947-5-1, UL 508 and CSA C22-2 N°14			
Terminal Marking:	according to EN 50013			

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SBC001699R1002
Declaration of Conformity - CE:	1SBD250881C2000

Classifications

ETIM 4:	EC001829 - Position switch modular
ETIM 5:	EC001829 - Position switch modular
UNSPSC:	39121500







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product	Code	Reference	Product link
LS40P53B11 Limit Switch	1SBV010553R1211	LS40P53B11	Buy on EAN