



Automatización Eléctrica Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking <u>HERE</u>

LS65M93D11



General Information					
Extended Product Type:	LS65M93D11				
Product ID:	1SBV013393R1411				
EAN:	3471522616531				
Catalog Description:	LS65M93D11 Limit Switch				
Long Description:	LS65M93D11 Limit Switch				
Categories					
Products » Low Voltage Products and	d Systems » Control Products » Sensors » Limit Switches				
Ordering					
EAN:	3471522616531				
Minimum Order Quantity:	10 piece				
Customs Tariff Number:	85369085				
Dimensions					
Product Net Width:	60 mm				
Product Net Weight:	0.255 kg				
Container Information	4				
Package Level 1 Units:	1 piece				
Package Level 1 Width:	200 mm				
Package Level 1 Height:	70 mm				
Package Level 1 Length:	45 mm				
Package Level 1 Gross Weight:	0.255 kg				
Package Level 1 EAN:	3471522616531				
Environmental					
Ambient Air Temperature:	Operation -25 +70 °C				
Ambient An Temperature.	Storage -30 +80 °C				
Resistance to Shock acc. to IEC 60068-2-27:	Half-sine Pulse for 11 ms, No Change in Contact Position 50 m/s ²				
	25g (10 to 500 Hz) no change in position of contacts greater than 100 μs				
60068-2-6:					
Technical UL/CSA					
Pilot Duty of Contact Elements acc.	4600				
UL508:	Q600				
Additional Information					
Action Type of the Contact Element	non-overlapping slow action contacts				
(acc. to IEC 60947-5-1): Actuation Speed:	acc. to IEC 60947-5-1 Max. 1.00 m/s				
Aduation opecu.	acc. to IEC 60947-5-1 Mia. 1.00 M/s				
Actuation Torque:	acc. to IEC 60947-5-1 Min. 0.18 N⋅m				
Actuator Type:	stainless steel coil spring rod				
Angular Head Adjustment:	adjustable head every 90°				
Angular Lever Adjustment:	none				
Climatic Withstand:	according to IEC 68-2-3 and salty mist according to IEC 68-2-11				
Connecting Capacity:	AWG 20 AWG 14 0.5 2.5 mm ²				
open position):	M3.5 (+,-) pozidriv 2 screw with cable clamp				
Consistency (Measured over 1 Million Operations):	0.05 mm				
Contact Element Form (acc. to IEC 60947-5-1):	Zb				
Conventional Free-air Thermal Current (I _{th}):	acc. to IEC 60947-5-1, q = 40 °C 10.0 A				
Degree of Protection:	acc. to IEC 60529 IP66				
Electrical Shock Protection acc. to IEC 536:	Class I				
IIT Publishing Status:	Level 0 - Information enabled				

Load Factor:	.5			
Maximum Electrical Switching Frequency:	3600 cycles per hour			
Mechanical Durability:	10 million			
Mounting by Screws (not supplied):	2 x M5 screws			
Mounting Position:	all positions are authorised			
Movement to be Detected:	Multidirectional Translation Movement			
Number and Type of Bottom Cable Glands:	1/2 NPT cable gland			
Number of Auxiliary Contacts NC:	1			
Number of Auxiliary Contacts NO:	1			
Positive Opening Operation of NC Contact(s):	No			
Product Main Type:	LS70			
Product Name:	Limit Switch			
Rated Frequency (f):	Supply Circuit 50 Hz Supply Circuit 60 Hz			
Rated Impulse Withstand Voltage (U _{imp}):	6 kV			
Rated Insulation Voltage (Ui):	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V acc. to UL/CSA 600 V			
Rated Operational Current AC-15 (I _e):	(130 V) 5.5 A (230 V) 3.1 A (240 V) 3 A (24 V) 10 A (400 V) 1.8 A			
Rated Operational Current DC-13 (I _e):	(110 V) 0.6 / 66 A (24 V) 2.8 / 67.2 A (250 V) 0.27 / 67.5 A			
Resistance Between Contacts:	25 mΩ			
Standards:	IEC 60947-1, IEC 60947-5-1, EN 60947-1, EN 60947-5-1, UL 508 and CSA C22-2 N°14			
Terminal for Protective Conductor:	M 3.5 (+,-) pozidriv 2 screw with cable clamp			
Terminal Marking:	according to EN 50013			

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	AC1300
Declaration of Conformity - CE:	1SBD250881C2000

Classifications

ETIM 4:	EC001829 - Position switch modular
ETIM 5:	EC001829 - Position switch modular







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product	Code	Reference	Product link
LS65M93D11 Limit Switch	1SBV013393R1411	LS65M93D11	Buy on EAN