



**Automatización Eléctrica**

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

## General Information

Extended Product Type:	OS630D03P
Product ID:	1SCA022825R2830
EAN:	6417019283432
Catalog Description:	OS630D03P Switch fuse
Long Description:	Including terminal bolt kit, a black ON-OFF plastic handle and shaft as standard. The handle is IP65 protected, padlockable in the OFF-position and with door interlock in the ON-position. The shaft is adjustable for a range of installation depths.

## Categories

Products » Low Voltage Products and Systems » Switches » Switch Fuses

## Ordering

EAN:	6417019283432
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080

## Dimensions

Product Net Width:	343 mm
Product Net Height:	306 mm
Product Net Depth:	233 mm
Product Net Weight:	13.5 kg

## Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	328 mm
Package Level 1 Height:	260 mm
Package Level 1 Length:	365 mm
Package Level 1 Gross Weight:	13.5 kg
Package Level 1 EAN:	6417019283432

## Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-05-01
--------------	--

## Additional Information

Conventional Free-air Thermal Current ( $I_{th}$ ):	$q = 40\text{ °C}$ 630 A
Conventional Thermal Current ( $I_{the}$ ):	Fully Enclosed 570 A
Fuse Size:	3
Fuse System:	DIN
Fuse Type:	DIN
Handle Type:	Pistol Handle
IIT Publishing Status:	Level 0 - Information enabled
Includes:	Handle and Shaft
Mounting Type:	Normal
Number of Poles:	3
Operating Mechanism:	Mechanism at the end of the switch
Operating Mode:	Front Operated
Pollution Degree:	3
Position of Line Terminals:	Top In - Bottom Out
Power Loss:	at Rated Operating Conditions per Pole 46 W
Product Main Type:	OS630
Product Name:	Switch fuse
Rated Impulse Withstand Voltage ( $U_{imp}$ ):	12 kV
Rated Insulation Voltage ( $U_i$ ):	1000 V
Rated Operational Current AC-21A ( $I_e$ ):	(380 ... 415 V) 630 A (500 V) 630 A (690 V) 630 A
Rated Operational Current AC-22A ( $I_e$ ):	(380 ... 415 V) 630 A (500 V) 630 A

	(690 V) 630 A
Rated Operational Current AC-23A (I <sub>e</sub> ):	(690 V) 630 A (500 V) 630 A (380 ... 415 V) 630 A
Rated Operational Power AC-23A (P <sub>e</sub> ):	(220 ... 240 V) 200 kW (400 V) 355 kW (415 V) 355 kW (500 V) 450 kW (690 V) 630 kW
Rated Operational Voltage:	690 V AC
Standards:	IEC
Terminal Type:	Lug terminals
Terminal Width:	39 mm
Tightening Torque:	acc. IEC 60947-1 50 ... 75 N·m

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SCC311013C0201
Declaration of Conformity - CE:	1SCC311112D0201
RoHS Information:	1SCC311108D0202

Classifications

E-nummer:	3172091
ETIM 5:	EC001040 - Fuse switch disconnecter
Object Classification Code:	Q





**Automatización Eléctrica**  
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
OS630D03P Switch fuse	1SCA022825R2830	OS630D03P	<a href="#">Buy on EAN</a>