Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE

OSM125GD3M230C

General Information

Extended Product Type:	OSM125GD3M230C
Product ID:	1SCA116674R1001
EAN:	6417019487700
Catalog Description:	OSM125GD3M230C Motorized switch fuse
Long Description:	Including a handle for manual operation, bolt kit with nut and washers for all terminals (100A…1250A), male connectors for control circuit and a handle and spare fuse storage clip.

Categories

Products » Low Voltage Products and Systems » Switches » Motorized Switch Fuses

Ordering

EAN:	6417019487700
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080

Dimensions

Product Net Width:	290 mm
Product Net Height:	206 mm
Product Net Depth:	140 mm
Product Net Weight:	4.1 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	175 mm
Package Level 1 Height:	235 mm
Package Level 1 Length:	360 mm
Package Level 1 Gross Weight:	4.1 kg
Package Level 1 EAN:	6417019487700

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-07-01

Additional Information

Conventional Free-air Thermal Current (I_{th}):	q = 40 °C 125 A
Fuse Size:	000, 00
Fuse System:	DIN
Fuse Type:	DIN
IIT Publishing Status:	Level 0 - Information enabled
Number of Poles:	3
Operating Mechanism:	Mechanism at the end of the switch
Pollution Degree:	3
Position of Line Terminals:	Top In - Bottom Out
Power Loss:	at Rated Operating Conditions per Pole 5 W
Product Main Type:	OSM160
Product Name:	Motorized switch fuse
Rated Impulse Withstand Voltage (U_{imp}):	12 kV
Rated Insulation Voltage (U_i):	1000 V
Rated Operational Current AC-21A (I_e):	(380 ... 415 V) 125 A (500 V) 125 A (690 V) 125 A
Rated Operational Current AC-22A (I_e):	(380 ... 415 V) 125 A (500 V) 125 A (690 V) 125 A
Rated Operational Current AC-23A (I_e):	(380 ... 415 V) 125 A (500 V) 125 A (690 V) 125 A
Rated Operational Power AC-23A (P_e):	(220 ... 240 V) 37 kW (400 V) 55 kW

	(415 V) 55 kW (500 V) 75 kW (690 V) 110 kW
Rated Operational Voltage:	1000 V
Rated Short-time Withstand Current (I_{cw}):	for 1 s 5 kiloampere rms

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SCC311013C0201

Classifications

ETIM 5:	EC001040 - Fuse switch disconnector
Object Classification Code:	Q

Automatización Eléctrica
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
OSM125GD3M230C Motorized switch fuse	1SCA116674R1001	OSM125GD3M230C	Buy on EAN