



**Automatización Eléctrica**

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

### General Information

|                        |   |
|------------------------|---|
| Extended Product Type: | T2L 160 TMD1,6-16 4p F F  |
| Product ID:            | 1SDA051094R1  |
| EAN:                   | 8015644515164   |
| Catalog Description:   | T2L 160 TMD1,6-16 4p F F  |
| Long Description:      | C.BREAKER TMAX T2L 160 FIXED FOUR-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMD R 1,6-16 A |

### Categories

Products » Low Voltage Products and Systems » Circuit Breakers » Moulded Case Circuit Breakers » Tmax T

### Ordering

|                         |               |
|-------------------------|---------------|
| EAN:                    | 8015644515164 |
| Minimum Order Quantity: | 1 piece       |
| Customs Tariff Number:  | 85362090      |

### Dimensions

|                     |         |
|---------------------|---------|
| Product Net Width:  | 120 mm  |
| Product Net Height: | 130 mm  |
| Product Net Depth:  | 70 mm   |
| Product Net Weight: | 1.45 kg |

### Container Information

|                               |               |
|-------------------------------|---------------|
| Package Level 1 Units:        | 1 piece       |
| Package Level 1 Width:        | 128 mm        |
| Package Level 1 Height:       | 135 mm        |
| Package Level 1 Length:       | 143 mm        |
| Package Level 1 Gross Weight: | 1.55 kg       |
| Package Level 1 EAN:          | 8015644515164 |

### Environmental

|              |  |
|--------------|--|
| RoHS Status: | Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-07-01 |
|--------------|--|

### Additional Information

|  |   |
|--|---|
| Electrical Durability:                                       | 8000 cycle<br>120 cycles per hour   |
| IIT Publishing Status:                                       | Level 0 - Information enabled   |
| Mechanical Durability:                                       | 25000 cycle<br>240 cycles per hour  |
| Number of Poles:   | 4   |
| Power Loss:  | at Rated Operating Conditions per Pole 2,1 W  |
| Product Main Type:   | SACE Tmax T   |
| Product Name:  | Automatic Circuit Breaker   |
| Product Type:  | CB  |
| Rated Current ( $I_n$ ):                                     | 1.6 A   |
| Rated Impulse Withstand Voltage ( $U_{imp}$ ):               | 8 kV  |
| Rated Insulation Voltage ( $U_i$ ):                          | 800 V   |
| Rated Operational Voltage:                                   | 690 V AC<br>500 V DC  |
| Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ ):  | (220 V AC) 100 kA<br>(230 V AC) 100 kA<br>(380 V AC) 70 kA<br>(400 V AC) 70 kA<br>(415 V AC) 70 kA<br>(440 V AC) 56 kA<br>(500 V AC) 37,5 kA<br>(690 V AC) 7,5 kA |
| Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ ): | (220 V AC) 12 kA<br>(230 V AC) 12 kA<br>(380 V AC) 85 kA<br>(400 V AC) 85 kA<br>(415 V AC) 85 kA  |

(440 V AC) 75 kA  
(500 V AC) 50 kA  
(690 V AC) 10 kA  
(250 V DC) 2 Poles in Series 85 kA  
(250 V DC) 3 Poles in Series 100 kA  
(500 V DC) 3 Poles in Series 85 kA

**Rated Uninterrupted Current ( $I_u$ ):** 160 A

**Release Type:** TM

**Standards:** IEC 60947

**Sub-type:** T2

**Suitable For:** T2

**Suitable for Product Class:** Moulded Case Circuit Breakers

**Terminal Connection Type:** Fixed Circuit-Breakers  
Front

**Test Voltage at Industrial Frequency for 1 Minute:** 3000 V

**Test Voltage Max ( $U_{test}$ ):** 3000 V

**Version:** F

### Certificates and Declarations (Document Number)

**Data Sheet, Technical Information:** 1SDC210004D0203

**Data Sheet, Technical Information (Part 2):** 1SDM000030R0001

**Declaration of Conformity - CE:** 1SDL000165R0002

**GL Certificate:** 1SDL000163R0059

**RoHS Information:** 1SDL000200R0001

### Classifications

**Object Classification Code:** Q

**UNSPSC:** 39121100





**Automatización Eléctrica**  
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

| Product                  | Code         | Reference | Product link               |
|--------------------------|--------------|-----------|----------------------------|
| T2L 160 TMD1,6-16 4p F F | 1SDA051094R1 | T2L160    | <a href="#">Buy on EAN</a> |