



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

| | |
|------------------------|---|
| Extended Product Type: | T3D 250 4p F F |
| Product ID: | 1SDA051328R1 |
| EAN: | 8015644517496 |
| Catalog Description: | T3D 250 4p F F |
| Long Description: | SWITCH-DISCONNECTOR TMAX T3D 250 FIXED FOUR-POLE WITH FRONT TERMINALS |

Categories

Products » Low Voltage Products and Systems » Circuit Breakers » Moulded Case Circuit Breakers » Tmax T

Ordering

| | |
|-------------------------|---------------|
| EAN: | 8015644517496 |
| Minimum Order Quantity: | 1 piece |
| Customs Tariff Number: | 85362090 |

Dimensions

| | |
|---------------------|--------|
| Product Net Width: | 140 mm |
| Product Net Height: | 150 mm |
| Product Net Depth: | 70 mm |
| Product Net Weight: | 2 kg |

Container Information

| | |
|-------------------------------|---------------|
| Package Level 1 Units: | 1 piece |
| Package Level 1 Width: | 155 mm |
| Package Level 1 Height: | 190 mm |
| Package Level 1 Length: | 155 mm |
| Package Level 1 Gross Weight: | 2.1 kg |
| Package Level 1 EAN: | 8015644517496 |

Environmental

| | |
|--------------|--|
| RoHS Status: | Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-07-01 |
|--------------|--|

Additional Information

| | |
|--|---|
| IIT Publishing Status: | Level 0 - Information enabled |
| Mechanical Durability: | 25000 cycle 120 cycles per hour |
| Number of Poles: | 4 |
| Power Loss: | at Rated Operating Conditions per Pole 17,8 W |
| Product Main Type: | SACE Tmax T |
| Product Name: | Switch-disconnector |
| Product Type: | SD |
| Rated Impulse Withstand Voltage (U_{imp}): | 8 kV |
| Rated Insulation Voltage (U_i): | 800 V |
| Rated Operational Voltage: | 690 V AC 500 V DC |
| Rated Short-time Withstand Current (I_{cw}): | for 1 s 3,6 A |
| Rated Uninterrupted Current (I_U): | 250 A |
| Standards: | IEC 60947 |
| Sub-type: | T3 |
| Suitable For: | T3 |
| Suitable for Product Class: | Moulded Case Circuit Breakers |
| Terminal Connection Type: | Fixed Circuit-Breakers Front |
| Test Voltage at Industrial Frequency for 1 Minute: | 3000 V |
| Test Voltage Max (U_{test}): | 3000 V |
| Version: | F |

Certificates and Declarations (Document Number)

Data Sheet, Technical Information: 1SDC210004D0203

Data Sheet, Technical Information (Part 2): 1SDM000030R0001

Declaration of Conformity - CE: 1SDL000165R0003

RoHS Information: 1SDL000200R0001

Classifications

Object Classification Code: Q

UNSPSC: 39121100





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

| Product | Code | Reference | Product link |
|----------------|--------------|-----------|----------------------------|
| T3D 250 4p F F | 1SDA051328R1 | T3D250 | Buy on EAN |