



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

| | |
|------------------------|--|
| Extended Product Type: | T5N 400 TMA 320-3200 3p F F |
| Product ID: | 1SDA054436R1 |
| EAN: | 8015644555405 |
| Catalog Description: | T5N 400 TMA 320-3200 3p F F |
| Long Description: | C.BREAKER TMAX T5N 400 FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMA R 320 I3=1600...3200 A |

Categories

Products » Low Voltage Products and Systems » Circuit Breakers » Moulded Case Circuit Breakers » Tmax T

Ordering

| | |
|-------------------------|---------------|
| EAN: | 8015644555405 |
| Minimum Order Quantity: | 1 piece |
| Customs Tariff Number: | 85362090 |

Dimensions

| | |
|---------------------|----------|
| Product Net Width: | 140 mm |
| Product Net Height: | 205 mm |
| Product Net Depth: | 103.5 mm |
| Product Net Weight: | 4.8 kg |

Container Information

| | |
|-------------------------------|---------------|
| Package Level 1 Units: | 1 piece |
| Package Level 1 Width: | 248 mm |
| Package Level 1 Height: | 240 mm |
| Package Level 1 Length: | 285 mm |
| Package Level 1 Gross Weight: | 4.8 kg |
| Package Level 1 EAN: | 8015644555405 |

Environmental

| | |
|--------------|--|
| RoHS Status: | Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-07-01 |
|--------------|--|

Additional Information

| | |
|--|--|
| Electrical Durability: | 7000 cycle 60 cycles per hour |
| IIT Publishing Status: | Level 0 - Information enabled |
| Mechanical Durability: | 20000 cycle 120 cycles per hour |
| Number of Poles: | 3 |
| Power Loss: | at Rated Operating Conditions per Pole 13,6 W |
| Product Main Type: | SACE Tmax T |
| Product Name: | Automatic Circuit Breaker |
| Product Type: | CB |
| Rated Current (I_n): | 320 A |
| Rated Impulse Withstand Voltage (U_{imp}): | 8 kV |
| Rated Insulation Voltage (U_i): | 1000 V |
| Rated Operational Voltage: | 690 V AC 750 V DC |
| Rated Service Short-Circuit Breaking Capacity (I_{cs}): | (220 V AC) 70 kA (230 V AC) 70 kA (380 V AC) 36 kA (400 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 30 kA (500 V AC) 25 kA (690 V AC) 20 kA |
| Rated Short-time Withstand Current (I_{cw}): | for 1 s 5 A |
| Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}): | (220 V AC) 7 kA (230 V AC) 7 kA (380 V AC) 36 kA |

(400 V AC) 36 kA
(415 V AC) 36 kA
(440 V AC) 30 kA
(500 V AC) 25 kA
(690 V AC) 20 kA
(250 V DC) 2 Poles in Series 36 kA
(250 V DC) 3 Poles in Series 25 kA
(500 V DC) 3 Poles in Series 16 kA

| | |
|---|---------------------------------|
| Rated Uninterrupted Current (I_u): | 400 A |
| Release Type: | TM |
| Standards: | IEC 60947 |
| Sub-type: | T5 |
| Suitable For: | T5 |
| Suitable for Product Class: | Moulded Case Circuit Breakers |
| Terminal Connection Type: | Fixed Circuit-Breakers Front |
| Test Voltage at Industrial Frequency for 1 Minute: | 3500 V |
| Test Voltage Max (U_{test}): | 3500 V |
| Version: | F |

Certificates and Declarations (Document Number)

| | |
|---|-----------------|
| Data Sheet, Technical Information: | 1SDC210004D0203 |
| Declaration of Conformity - CE: | 1SDL000165R0005 |
| RoHS Information: | 1SDL000200R0001 |

Classifications

| | |
|------------------------------------|---|
| ETIM 4: | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| ETIM 5: | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| Object Classification Code: | Q |
| UNSPSC: | 39121100 |





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

| Product | Code | Reference | Product link |
|-----------------------------|--------------|------------------|----------------------------|
| T5N 400 TMA 320-3200 3p F F | 1SDA054436R1 | T5N400 | Buy on EAN |