



**Automatización Eléctrica**

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

# T4V250 TMA250-2500 4pFFC1150VAC/DC N100%



## General Information

Extended Product Type:	T4V250 TMA250-2500 4pFFC1150VAC/DC N100%
Product ID:	1SDA054504R1
EAN:	8015644556068
Catalog Description:	T4V250 TMA250-2500 4pFFC1150VAC/DC N100%
Long Description:	C.BREAKER TMAX T4V 250 1150V AC-1000V DC FIXED FOUR-POLE WITH FRONT TERMINALS FOR CABLE Cu AND THERMOMAGNETIC RELEASE TMA R 250-2500 A FULLY RATED NEUTRAL

## Categories

Products » Low Voltage Products and Systems » Circuit Breakers » Moulded Case Circuit Breakers » Tmax T

## Ordering

EAN:	8015644556068
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362090

## Dimensions

Product Net Width:	140 mm
Product Net Height:	205 mm
Product Net Depth:	103.5 mm
Product Net Weight:	3.05 kg

## Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	248 mm
Package Level 1 Height:	240 mm
Package Level 1 Length:	285 mm
Package Level 1 Gross Weight:	3.5 kg
Package Level 1 EAN:	8015644556068

## Additional Information

Electrical Durability:	8000 cycle 120 cycles per hour
Mechanical Durability:	20000 cycle 240 cycles per hour
Number of Poles:	4
Power Loss:	at Rated Operating Conditions per Pole 13,7 W
Product Main Type:	SACE Tmax T
Product Name:	Automatic Circuit Breaker
Product Type:	CB
Rated Current ( $I_n$ ):	250 A
Rated Impulse Withstand Voltage ( $U_{imp}$ ):	8 kV
Rated Insulation Voltage ( $U_i$ ):	1000 V
Rated Operational Voltage:	1000 V AC 1000 V DC
Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ ):	(1000 V AC) 12 kA (1150 V AC) 6 kA (1000 V DC) 20 kA
Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ ):	(1000 V AC) 20 kA (1150 V AC) 12 kA (1000 V DC) 40 kA
Rated Uninterrupted Current ( $I_u$ ):	250 A
Release Type:	TM
Standards:	IEC 60947
Sub-type:	T4
Terminal Connection Type:	Fixed Circuit-Breakers Front for Copper Cables
Test Voltage Max ( $U_{test}$ ):	3500 V
Version:	F

## Certificates and Declarations (Document Number)

---

**Data Sheet, Technical Information:** 1SDC210023D0201

**Declaration of Conformity - CE:** 1SDL000165R0004

**GL Certificate:** 1SDL000163R0061

---

## Classifications

---


**ETIM 4:** EC000228 - Power circuit-breaker for trafo/generator/installation prot.

**ETIM 5:** EC000228 - Power circuit-breaker for trafo/generator/installation prot.

**Object Classification Code:** Q

**UNSPSC:** 39121100

---





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
T4V250 TMA250-2500 4pFFC1150VAC/DC N100%	1SDA054504R1	T4V250 1000V	<a href="#">Buy on EAN</a>