



**Automatización Eléctrica**

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

## General Information

|                        |   |
|------------------------|---|
| Extended Product Type: | E1N 1250 PR122/P-LSI In=1250A 3p F HR   |
| Product ID:            | 1SDA055732R1  |
| EAN:                   | 8015644570729   |
| Catalog Description:   | E1N 1250 PR122/P-LSI In=1250A 3p F HR   |
| Long Description:      | SACE EMAX CIRCUIT-BREAKER E1N 1250A THRE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSI R1250 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED |

## Categories

Products » Low Voltage Products and Systems » Circuit Breakers » Air Circuit Breakers » Emax

## Ordering

|                         |               |
|-------------------------|---------------|
| EAN:                    | 8015644570729 |
| Minimum Order Quantity: | 1 piece       |
| Customs Tariff Number:  | 85362090      |

## Dimensions

|                     |        |
|---------------------|--------|
| Product Net Width:  | 296 mm |
| Product Net Height: | 418 mm |
| Product Net Depth:  | 302 mm |
| Product Net Weight: | 40 kg  |

## Container Information

|                               |               |
|-------------------------------|---------------|
| Package Level 1 Units:        | 1 piece       |
| Package Level 1 Width:        | 515 mm        |
| Package Level 1 Height:       | 600 mm        |
| Package Level 1 Length:       | 515 mm        |
| Package Level 1 Gross Weight: | 50 kg         |
| Package Level 1 EAN:          | 8015644570729 |

## Additional Information

|  |  |
|--|--|
| Electrical Durability:                                       | 10000 cycle<br>30 cycles per hour  |
| Mechanical Durability:                                       | 25000 cycle<br>60 cycles per hour  |
| Number of Poles:   | 3  |
| Power Loss:  | at Rated Operating Conditions per Pole 150 W   |
| Product Main Type:   | SACE Emax  |
| Product Name:  | Automatic Circuit Breaker  |
| Product Type:  | CB   |
| Rated Current ( $I_n$ ):                                     | 1250 A   |
| Rated Impulse Withstand Voltage ( $U_{imp}$ ):               | 12 kV  |
| Rated Insulation Voltage ( $U_i$ ):                          | 1000 V   |
| Rated Operational Current ( $I_e$ ):                         | 1250 A   |
| Rated Operational Voltage:                                   | 690 V AC   |
| Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ ):  | (220 V AC) 50 kA<br>(230 V AC) 50 kA<br>(400 V AC) 50 kA<br>(415 V AC) 50 kA<br>(440 V AC) 50 kA<br>(500 V AC) 50 kA<br>(660 V AC) 50 kA<br>(380 V AC) 50 kA<br>(690 V AC) 50 kA |
| Rated Short-time Withstand Current ( $I_{cw}$ ):             | for 1 s 50 kA<br>for 3 s 36 kA   |
| Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ ): | (220 V AC) 50 kA<br>(230 V AC) 50 kA<br>(380 V AC) 50 kA<br>(400 V AC) 50 kA<br>(415 V AC) 50 kA<br>(440 V AC) 50 kA<br>(500 V AC) 50 kA   |

(525 V AC) 50 kA  
(660 V AC) 50 kA  
(690 V AC) 50 kA

|   |  |
|---|--|
| <b>Rated Uninterrupted Current (I<sub>u</sub>):</b> | 1250 A   |
| <b>Rated Voltage (U<sub>r</sub>):</b>               | 690 V  |
| <b>Release Type:</b>                                | EL   |
| <b>Standards:</b>                                   | IEC 60947                                      |
| <b>Sub-type:</b>                                    | E1   |
| <b>Terminal Connection Type:</b>                    | Fixed Circuit-Breakers<br>Rear flat Horizontal |
| <b>Version:</b>                                     | F  |

#### Certificates and Declarations (Document Number)

|   |                 |
|---|-----------------|
| <b>Data Sheet, Technical Information:</b> | 1SDC200006D0209 |
| <b>Declaration of Conformity - CE:</b>    | 1SDL000165R0013 |

#### Classifications

|                                    |   |
|------------------------------------|---|
| <b>ETIM 4:</b>                     | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| <b>ETIM 5:</b>                     | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| <b>Object Classification Code:</b> | Q   |
| <b>UNSPSC:</b>                     | 39120000  |





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

| <b>Product</b>                        | <b>Code</b>  | <b>Reference</b> | <b>Product link</b>        |
|---------------------------------------|--------------|------------------|----------------------------|
| E1N 1250 PR122/P-LSI In=1250A 3p F HR | 1SDA055732R1 | E1N1250          | <a href="#">Buy on EAN</a> |