



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

Extended Product Type:	E1N 1250 PR121/P-LI In=1250A 3p W MP
Product ID:	1SDA055744R1
EAN:	8015644570842
Catalog Description:	E1N 1250 PR121/P-LI In=1250A 3p W MP
Long Description:	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E1N 1250A THREE-POLE OVERCURRENT RELEASE PR121/P-LI R1250 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Categories

Products » Low Voltage Products and Systems » Circuit Breakers » Air Circuit Breakers » Emax

Ordering

EAN:	8015644570842
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362090

Dimensions

Product Net Width:	324 mm
Product Net Height:	461 mm
Product Net Depth:	396.5 mm
Product Net Weight:	44 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	515 mm
Package Level 1 Height:	600 mm
Package Level 1 Length:	515 mm
Package Level 1 Gross Weight:	55 kg
Package Level 1 EAN:	8015644570842

Additional Information

Electrical Durability:	10000 cycle 30 cycles per hour
Mechanical Durability:	25000 cycle 60 cycles per hour
Number of Poles:	3
Power Loss:	at Rated Operating Conditions per Pole 230 W
Product Main Type:	SACE Emax
Product Name:	Automatic Circuit Breaker
Product Type:	CBMP
Rated Current (I_n):	1250 A
Rated Impulse Withstand Voltage (U_{imp}):	12 kV
Rated Insulation Voltage (U_i):	1000 V
Rated Operational Current (I_e):	1250 A
Rated Operational Voltage:	690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(220 V AC) 50 kA (230 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 50 kA (660 V AC) 50 kA (380 V AC) 50 kA (690 V AC) 50 kA
Rated Short-time Withstand Current (I_{cw}):	for 1 s 50 kA for 3 s 36 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V AC) 50 kA (230 V AC) 50 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 50 kA

(525 V AC) 50 kA
(660 V AC) 50 kA
(690 V AC) 50 kA

Rated Uninterrupted Current (I_u):	1250 A
Rated Voltage (U_r):	690 V
Release Type:	EL
Standards:	IEC 60947
Sub-type:	E1
Terminal Connection Type:	Withdrawable Circuit-Breakers
Version:	W

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SDC200006D0209
Declaration of Conformity - CE:	1SDL000165R0013

Classifications

ETIM 4:	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 5:	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
Object Classification Code:	Q
UNSPSC:	39120000





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
E1N 1250 PR121/P-LI In=1250A 3p W MP	1SDA055744R1	E1N1250	Buy on EAN