



Automatización Eléctrica Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking <u>HERE</u>

X1B/MS 1000 4p W MP



General Information

Extended Product Type:	X1B/MS 1000 4p W MP
Product ID:	1SDA062055R1
EAN:	8015644645991
Catalog Description:	X1B/MS 1000 4p W MP
Long Description:	MOVING PART FOR C.BREAKER SWITCH-DISCONNECTOR EMAX X1B/MS 1000 FOUR- POLE

Categories

Products » Low Voltage Products and Systems » Circuit Breakers » Air Circuit Breakers » Emax

Ordering

Ordering	
EAN:	8015644645991
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362090
Dimensions	
Product Net Width:	354 mm
Product Net Height:	343 mm
Product Net Depth:	254 mm
Product Net Weight:	18 kg
Container Information	
Package Level 1 Units:	1 piece
Package Level 1 Width:	385 mm
Package Level 1 Height:	350 mm
Package Level 1 Length:	400 mm
Package Level 1 Gross Weight:	19.5 kg
Package Level 1 EAN:	8015644609139
Environmental	
DoUS Statuo	Planned to follow ELL Directive 2002/05/EC August 19, 2005 and amondment after 2007 02
RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007 Q2
Additional Information	
Additional Information Number of Poles:	4
Additional Information Number of Poles: Power Loss:	4 at Rated Operating Conditions per Pole 162 W
Additional Information Number of Poles: Power Loss: Product Main Type:	4 at Rated Operating Conditions per Pole 162 W SACE Emax
Additional Information Number of Poles: Power Loss: Product Main Type: Product Name:	4 at Rated Operating Conditions per Pole 162 W SACE Emax Switch-disconnector
Additional Information Number of Poles: Power Loss: Product Main Type: Product Name: Product Type:	4 at Rated Operating Conditions per Pole 162 W SACE Emax Switch-disconnector SDMP
Additional Information Number of Poles: Power Loss: Product Main Type: Product Name: Product Type: Rated Current (I _n):	4 at Rated Operating Conditions per Pole 162 W SACE Emax Switch-disconnector SDMP 1000 A
Additional Information Number of Poles: Power Loss: Product Main Type: Product Name: Product Type:	4 at Rated Operating Conditions per Pole 162 W SACE Emax Switch-disconnector SDMP 1000 A
Additional Information Number of Poles: Power Loss: Product Main Type: Product Name: Product Type: Rated Current (I _n): Rated Short-time Withstand Current	4 at Rated Operating Conditions per Pole 162 W SACE Emax Switch-disconnector SDMP 1000 A
Additional Information Number of Poles: Power Loss: Product Main Type: Product Name: Product Name: Product Type: Rated Current (I _n): Rated Short-time Withstand Current (I _{cw}):	4 at Rated Operating Conditions per Pole 162 W SACE Emax Switch-disconnector SDMP 1000 A t for 1 s 42 kA
Additional Information Number of Poles: Power Loss: Product Main Type: Product Name: Product Name: Product Type: Rated Current (I _n): Rated Short-time Withstand Current (I _{cw}): Rated Uninterrupted Current (I _u):	4 at Rated Operating Conditions per Pole 162 W SACE Emax Switch-disconnector SDMP 1000 A t for 1 s 42 kA 1000 A
Additional Information Number of Poles: Power Loss: Product Main Type: Product Name: Product Type: Rated Current (I _n): Rated Short-time Withstand Current (I _{cw}): Rated Uninterrupted Current (I _u): Rated Voltage (U _r):	4 at Rated Operating Conditions per Pole 162 W SACE Emax Switch-disconnector SDMP 1000 A tor 1 s 42 kA 1000 A 690 V
Additional Information Number of Poles: Power Loss: Product Main Type: Product Name: Product Type: Rated Current (In): Rated Short-time Withstand Current (I _{cw}): Rated Uninterrupted Current (I _u): Rated Voltage (U _r): Standards:	4 at Rated Operating Conditions per Pole 162 W SACE Emax Switch-disconnector SDMP 1000 A tor 1 s 42 kA 1000 A 690 V IEC 60947
Additional Information Number of Poles: Power Loss: Product Main Type: Product Name: Product Type: Rated Current (In): Rated Short-time Withstand Current (Icw): Rated Uninterrupted Current (Iu): Rated Voltage (Ur): Standards: Sub-type:	4 at Rated Operating Conditions per Pole 162 W SACE Emax Switch-disconnector SDMP 1000 A 1000 A i for 1 s 42 kA 1000 A 690 V IEC 60947 X1
Additional Information Number of Poles: Power Loss: Product Main Type: Product Name: Product Type: Rated Current (In): Rated Short-time Withstand Current (Icw): Rated Uninterrupted Current (Iu): Rated Voltage (Ur): Standards: Sub-type: Terminal Connection Type:	4 at Rated Operating Conditions per Pole 162 W SACE Emax Switch-disconnector SDMP 1000 A 1000 A for 1 s 42 kA 1000 A 690 V IEC 60947 X1 Withdrawable Circuit-Breakers
Additional Information Number of Poles: Power Loss: Product Main Type: Product Name: Product Type: Rated Current (In): Rated Short-time Withstand Current (Icw): Rated Uninterrupted Current (Iu): Rated Voltage (Ur): Standards: Sub-type: Terminal Connection Type:	4 at Rated Operating Conditions per Pole 162 W SACE Emax Switch-disconnector SDMP 1000 A tor 1 s 42 kA 1000 A 690 V IEC 60947 X1 Withdrawable Circuit-Breakers W
Additional Information Number of Poles: Power Loss: Product Main Type: Product Name: Product Type: Rated Current (In): Rated Short-time Withstand Current (Icw): Rated Uninterrupted Current (Iu): Rated Voltage (Ur): Standards: Sub-type: Terminal Connection Type: Version:	4 at Rated Operating Conditions per Pole 162 W SACE Emax Switch-disconnector SDMP 1000 A i for 1 s 42 kA 1000 A 690 V IEC 60947 X1 Withdrawable Circuit-Breakers W
Additional Information Number of Poles: Power Loss: Product Main Type: Product Name: Product Type: Rated Current (In): Rated Short-time Withstand Current (Icw): Rated Uninterrupted Current (Iu): Rated Voltage (Ur): Standards: Sub-type: Terminal Connection Type: Version:	4 at Rated Operating Conditions per Pole 162 W SACE Emax Switch-disconnector SDMP 1000 A i for 1 s 42 kA 1000 A 690 V IEC 60947 X1 Withdrawable Circuit-Breakers W
Additional Information Number of Poles: Power Loss: Product Main Type: Product Name: Product Type: Rated Current (In): Rated Short-time Withstand Current (I _{cw}): Rated Uninterrupted Current (I _u): Rated Voltage (U _r): Standards: Sub-type: Terminal Connection Type: Version:	4 at Rated Operating Conditions per Pole 162 W SACE Emax Switch-disconnector SDMP 1000 A i for 1 s 42 kA 1000 A 690 V IEC 60947 X1 Withdrawable Circuit-Breakers W

Classifications

ETIM 4:	EC000228 - Power circuit-breaker for trafo/generator/installation prot.		
ETIM 5:	EC000228 - Power circuit-breaker for trafo/generator/installation prot.		
Object Classification Code:	Q		
UNSPSC:	39120000		







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product	Code	Reference	Product link
X1B/MS 1000 4p W MP	1SDA062055R1	X1B/MS1000	Buy on EAN