



**Automatización Eléctrica**

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

## General Information

Extended Product Type:	T2S 160 PR221GP In=63A 4p F F
Product ID:	1SDA065361R1
EAN:	8015644681791
Catalog Description:	T2S 160 PR221GP In=63A 4p F F
Long Description:	C.BREAKER TMAX T2S 160 FIXED FOUR-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC PR221GP R 63

## Categories

Products » Low Voltage Products and Systems » Circuit Breakers » Moulded Case Circuit Breakers » Tmax T

## Ordering

EAN:	8015644681791
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362090

## Dimensions

Product Net Width:	120 mm
Product Net Height:	130 mm
Product Net Depth:	70 mm
Product Net Weight:	1.5 kg

## Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	128 mm
Package Level 1 Height:	135 mm
Package Level 1 Length:	143 mm
Package Level 1 Gross Weight:	1.6 kg
Package Level 1 EAN:	8015644681791

## Additional Information

Electrical Durability:	8000 cycle 120 cycles per hour
Mechanical Durability:	25000 cycle 240 cycles per hour
Number of Poles:	4
Power Loss:	at Rated Operating Conditions per Pole 3,5 W
Product Main Type:	SACE Tmax T
Product Name:	Automatic Circuit Breaker
Product Type:	CB
Rated Current (I <sub>n</sub> ):	63 A
Rated Impulse Withstand Voltage (U <sub>imp</sub> ):	8 kV
Rated Insulation Voltage (U <sub>i</sub> ):	800 V
Rated Operational Voltage:	690 V AC 500 V DC
Rated Service Short-Circuit Breaking Capacity (I <sub>cs</sub> ):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 45 kA (500 V AC) 30 kA (690 V AC) 7 kA
Rated Ultimate Short-Circuit Breaking Capacity (I <sub>cu</sub> ):	(220 V AC) 8.5 kA (230 V AC) 8.5 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 45 kA (500 V AC) 30 kA (690 V AC) 7 kA (250 V DC) 2 Poles in Series 50 kA (250 V DC) 3 Poles in Series 55 kA (500 V DC) 3 Poles in Series 50 kA

<b>Rated Uninterrupted Current (<math>I_u</math>):</b>	160 A
<b>Release Type:</b>	EL
<b>Standards:</b>	IEC 60947
<b>Sub-type:</b>	T2
<b>Terminal Connection Type:</b>	Fixed Circuit-Breakers Front
<b>Test Voltage Max (<math>U_{test}</math>):</b>	3000 V
<b>Version:</b>	F

---

### Certificates and Declarations (Document Number)

<b>Data Sheet, Technical Information:</b>	1SDC210033D0202
<b>Declaration of Conformity - CE:</b>	1SDL000165R0002
<b>GL Certificate:</b>	1SDL000163R0059

---

### Classifications

<b>Object Classification Code:</b>	Q
<b>UNSPSC:</b>	39121100





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

<b>Product</b>	<b>Code</b>	<b>Reference</b>	<b>Product link</b>
T2S 160 PR221GP In=63A 4p F F	1SDA065361R1	T2S160	<a href="#">Buy on EAN</a>