



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

Extended Product Type:	T8V 2500 PR332/P LSI In=2500A 3p F F
Product ID:	1SDA065783R1
EAN:	8015644686949
Catalog Description:	T8V 2500 PR332/P LSI In=2500A 3p F F
Long Description:	C.BREAKER TMAX T8V 2500 FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC PR332/P-LSI R 2500

Categories

Products » Low Voltage Products and Systems » Circuit Breakers » Moulded Case Circuit Breakers » Tmax T

Ordering

EAN:	8015644686949
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362090

Dimensions

Product Net Width:	427 mm
Product Net Height:	382 mm
Product Net Depth:	282 mm
Product Net Weight:	9.7 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	525 mm
Package Level 1 Height:	475 mm
Package Level 1 Length:	695 mm
Package Level 1 Gross Weight:	11.2 kg
Package Level 1 EAN:	8015644686949

Additional Information

Electrical Durability:	4000 cycle 20 cycles per hour
Mechanical Durability:	15000 cycle 60 cycles per hour
Number of Poles:	3
Power Loss:	at Rated Operating Conditions per Pole 73 W
Product Main Type:	SACE Tmax T
Product Name:	Automatic Circuit Breaker
Product Type:	CB
Rated Current (I _n):	2500 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV
Rated Insulation Voltage (U _i):	1000 V
Rated Operational Voltage:	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs}):	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 100 kA (500 V AC) 75 kA (690 V AC) 60 kA
Rated Short-time Withstand Current (I _{cw}):	for 1 s 40 A
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}):	(220 V AC) 1.3 kA (230 V AC) 1.3 kA (380 V AC) 130 kA (400 V AC) 130 kA (415 V AC) 130 kA (440 V AC) 130 kA (500 V AC) 100 kA (690 V AC) 80 kA
Rated Uninterrupted Current (I _u):	2500 A

Release Type:	EL
Standards:	IEC 60947
Sub-type:	T8
Terminal Connection Type:	Fixed Circuit-Breakers Front
Version:	F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SDC210023D0201
Declaration of Conformity - CE:	1SDL000165R0008

Classifications

ETIM 4:	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 5:	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
Object Classification Code:	Q





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
T8V 2500 PR332/P LSI In=2500A 3p F F	1SDA065783R1	T8V2500	Buy on EAN