



## Automatización Eléctrica Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking <u>HERE</u>

## RBR121-12VDC



## General Information

Extended Product Type:	RBR121-12VDC
Product ID:	1SNA645535R2600
EAN:	4013614508417
Catalog Description:	RBR121-12VDC Interface relay R600 1c/o,A1-A2=12VDC,250V/10mA-6A, LED
Long Description:	Spring relay RBR121 12vdc : 12vdc input / 1SPDT 10 mA upto 6A with led

## Categories

Products » Low Voltage Products and Systems » Control Products » Electronic Relays and Controls » Interface Relays and Optocouplers

EAN:    4013614508417      Minimum Order Quantity:    10 piece      Customs Tariff Number:    85364900      Dimensions    Product Net Width:      Product Net Width:    6 mm      Product Net Width:    6 nm      Product Net Bepth:    75 mm      Product Net Bepth:    73 mm      Package Level 1 Width:    73 mm      Package Level 1 Width:    73 mm      Package Level 1 Length:    80 mm      Package Level 1 EaN:    3472596455354      Technical    50 mm      Function:    Boxed interface relay R600      Sub-Function:    Relay with built in LED      Output:    1 c/o (SPDT) contact      Output Signal:    12 250 V AC/ 10 mA 6 A      Rated Control Supply Voltage (Ug):    12 V DC      Terminal Type:    Spring Terminals      Certificate:    cLR 248421      clc Cartificate:    cLR 24821      clc Cartificate:    cLR 24821	Ordering	
Customs Tariff Number:  85864900    Dimensions  Froduct Net Width:  6 mm    Product Net Height:  67.5 mm  Product Net Depth:  75 mm    Product Net Weight:  0.02 kg  Container Information    Package Level 1 Units:  10 piece  Package Level 1 Width:  73 mm    Package Level 1 Units:  10 piece  Package Level 1 Width:  73 mm    Package Level 1 Units:  10 piece  Package Level 1 Gross Weight:  0.23 kg    Package Level 1 Gross Weight:  0.23 kg  Package Level 1 EAN:  3472596455354    Technical  Function:  Boxed interface relay R600  Sub-Function:  Boxed interface relay R600    Sub-Function:  Relay with built in LED  Output  1 c/o (SPDT) contact  Output Signal:  1 2 250 V AC / 10 mA 6 A    Rated Control Supply Voltage (Up):  12 V DC  Terminal S  Certificate:  CSA Certificate:  CSA 254821  Colume Conton    CiR Certificate:  cRA 254821  Colume Contomity - CE:  ISND225048C1000  EAC Certificate:  CRA 254821  Colume Conton  CRA Certificate:  CRA 254821  Colume Conton  CRA Certificate:  CRA 254821  Colume Cont	<b>U</b>	4013614508417
Dimensions    Product Net Wildth:  6 mm    Product Net Height:  67.5 mm    Product Net Depth:  75 mm    Product Net Weight:  0.02 kg    Container Information	Minimum Order Quantity:	10 piece
Product Net Width:  6 mm    Product Net Height:  67.5 mm    Product Net Depth:  75 mm    Product Net Weight:  0.02 kg    Container Information    Package Level 1 Units:  10 piece    Package Level 1 Width:  73 mm    Package Level 1 Height:  71 mm    Package Level 1 Height:  71 mm    Package Level 1 Length:  80 mm    Package Level 1 Ength:  80 mm    Package Level 1 Ength:  3472596455354    Technical  Eunction:    Function:  Boxed interface relay R600    Sub-Function:  Relay with built in LED    Output:  1 c/o (SPDT) contact    Output Signal:  12 250 V AC / 10 mA 6 A    Rated Control Supply Voltage (Us):  12 V DC    Terminal Type:  Spring Terminals    Certificate:  c LR_25421    cUR Certificate:  c UR_E352056    Declaration of Conformity - CE:  ISND22504821000    EAC certificate:  LRS_0620042    UR Certificate:  LRS_0620042    UR Certificate:  UR_E352056    Declarations Coole:	Customs Tariff Number:	85364900
Product Net Width:  6 mm    Product Net Height:  67.5 mm    Product Net Depth:  75 mm    Product Net Weight:  0.02 kg    Container Information    Package Level 1 Units:  10 piece    Package Level 1 Width:  73 mm    Package Level 1 Height:  71 mm    Package Level 1 Height:  71 mm    Package Level 1 Length:  80 mm    Package Level 1 Ength:  80 mm    Package Level 1 Ength:  3472596455354    Technical  Eunction:    Function:  Boxed interface relay R600    Sub-Function:  Relay with built in LED    Output:  1 c/o (SPDT) contact    Output Signal:  12 250 V AC / 10 mA 6 A    Rated Control Supply Voltage (Us):  12 V DC    Terminal Type:  Spring Terminals    Certificate:  c LR_25421    cUR Certificate:  c UR_E352056    Declaration of Conformity - CE:  ISND22504821000    EAC certificate:  LRS_0620042    UR Certificate:  LRS_0620042    UR Certificate:  UR_E352056    Declarations Coole:		
Product Net Height:  67.5 mm    Product Net Depth:  75 mm    Product Net Weight:  0.02 kg    Container Information	Dimensions	
Product Net Deph:  75 mm    Product Net Weight:  0.02 kg    Container Information  Package Level 1 Units:  10 piece    Package Level 1 Units:  73 mm  Package Level 1 Height:  73 mm    Package Level 1 Height:  71 mm  Package Level 1 Height:  80 mm    Package Level 1 Gross Weight:  0.23 kg  Package Level 1 EAN:  3472596455354    Technical  Technical  Function:  Boxed interface relay R600  Sub-Function:  Relay with built in LED    Output:  1 c/o (SPDT) contact  Output:  1 c/o (SPDT) contact  Output:  1 c/o (SPDT) contact    Output Signal:  12 250 V AC / 10 mA 6 A  Rated Control Supply Voltage (Us):  1 2 V DC  Terminal S    Certificates and Declarations (Decument Number)  CSA Certificate:  CSA 254821  Current S2056  Curentificate:  UR E352056	Product Net Width:	6 mm
Product Net Weight:  0.02 kg    Container Information  Inits:  10 piece    Package Level 1 Units:  10 piece    Package Level 1 Height:  71 mm    Package Level 1 Height:  71 mm    Package Level 1 Height:  80 mm    Package Level 1 Cross Weight:  0.23 kg    Package Level 1 EAN:  3472596455354    Technical  Std>Function:    Function:  Relay with built in LED    Output:  1 c/o (SPDT) contact    Output:  1 c/o (SPDT)    Certificate:  CSA_254821    cdCertificate:  CSA_	Product Net Height:	67.5 mm
Container Information    Package Level 1 Units:  10 piece    Package Level 1 Width:  73 mm    Package Level 1 Height:  71 mm    Package Level 1 Length:  80 mm    Package Level 1 Cross Weight:  0.23 kg    Package Level 1 EAN:  3472596455354    Technical  Function:    Function:  Boxed interface relay R600    Sub-Function:  Relay with built in LED    Output:  1 c/o (SPDT) contact    Output Signal:  12 250 V AC / 10 mA 6 A    Rated Control Supply Voltage (Us):  12 V DC    Terminal Type:  Spring Terminals    Certificates and Declarations (Document Number)  CSA 254821    culk Certificate:  cUR E352056    Declaration of Conformity - CE:  1SND225048C1000    EAC EAU_CFR ME77.B.01634  LR Certificate:    LR Certificate:  LRS_0620042    UR Certificate:  UR_E352056	Product Net Depth:	75 mm
Package Level 1 Units:    10 piece      Package Level 1 Width:    73 mm      Package Level 1 Height:    71 mm      Package Level 1 Length:    80 mm      Package Level 1 Gross Weight:    0.23 kg      Package Level 1 EAN:    3472596455354      Technical	Product Net Weight:	0.02 kg
Package Level 1 Width:  73 mm    Package Level 1 Height:  71 mm    Package Level 1 Length:  80 mm    Package Level 1 Gross Weight:  0.23 kg    Package Level 1 EAN:  3472596455354    Technical	Container Information	
Package Level 1 Width:  73 mm    Package Level 1 Height:  71 mm    Package Level 1 Length:  80 mm    Package Level 1 Gross Weight:  0.23 kg    Package Level 1 EAN:  3472596455354    Technical	Package Level 1 Units:	10 piece
Package Level 1 Height:71 mmPackage Level 1 Length:80 mmPackage Level 1 Gross Weight:0.23 kgPackage Level 1 Gross Weight:0.23 kgPackage Level 1 EAN:3472596455354TechnicalFunction:Boxed interface relay R600Sub-Function:Relay with built in LEDOutput:1 c/c (SPDT) contactOutput Signal:12 250 V AC / 10 mA 6 ARated Control Supply Voltage (Us):12 V DCTerminal Type:Spring TerminalsCertificates and Declarations (Document Number)CSA Certificate:CJR_254821duCertificate:cUR_E352056Declaration of Conformity - CE:18ND225048C1000EAC Certificate:EAC RU_C-FR.ME77.B.01634LR Certificate:UR_E352056Object Classification Code:KETIM 4:EC001437 - Switching relayETIM 4:EC001437 - Switching relayUNSPSC:39121500	-	•
Package Level 1 Gross Weight:  0.23 kg    Package Level 1 EAN:  3472596455354    Technical  Function:    Function:  Boxed interface relay R600    Sub-Function:  Relay with built in LED    Output:  1 c/o (SPDT) contact    Output:  1 c/o (SPDT) contact    Output:  1 c/o (SPDT) contact    Output:  1 2 250 V AC / 10 mA 6 A    Rated Control Supply Voltage (Us):  12 V DC    Terminal Type:  Spring Terminals    Certificates and Declarations (Document Number)  CSA Certificate:    CSA Certificate:  CSA_254821    cuR Certificate:  cuR_E352056    Declaration of Conformity - CE:  1 SND225048C1000    EAC Certificate:  LRS_0620042    UR Certificate:  UR_E352056    Classifications  UR_E352056    Object Classification Code:  K    ETIM 4:  EC001437 - Switching relay    ETIM 5:  EC001437 - Switching relay    UNSPSC:  39121500	_	71 mm
Package Level 1 EAN:  3472596455354    Technical  Function:  Boxed interface relay R600    Sub-Function:  Relay with built in LED    Output:  1 c/o (SPDT) contact    Output Signal:  12 250 V AC / 10 mA 6 A    Rated Control Supply Voltage (Us):  12 V DC    Terminal Type:  Spring Terminals    Certificates and Declarations (Document Number)  CSA Certificate:    CSA Certificate:  CSA_254821    cUR Certificate:  cUR_E352056    Declaration of Conformity - CE:  1 SND225048C1000    EAC Certificate:  EAC_RU_C-FR.ME77.B.01634    LR Certificate:  UR_E352056    Celassifications  UR_E352056    Celassificate:  EAC_RU_C-FR.ME77.B.01634    LR Certificate:  UR_E352056    Classifications  UR_E352056    Diject Classification Code:  K <td< th=""><th>Package Level 1 Length:</th><th>80 mm</th></td<>	Package Level 1 Length:	80 mm
Technical    Function:  Boxed interface relay R600    Sub-Function:  Relay with built in LED    Output:  1 c/o (SPDT) contact    Output Signal:  12 250 V AC / 10 mA 6 A    Rated Control Supply Voltage (Us):  12 V DC    Terminal Type:  Spring Terminals    Certificates and Declarations (Document Number)  CSA Certificate:    CSA Certificate:  CSA_254821    cUR Certificate:  cUR_E352056    Declaration of Conformity - CE:  1 SND225048C1000    EAC Certificate:  EAC_RU_C-FR.ME77.B.01634    LR Certificate:  UR_E352056    Declaration of Conformity - CE:  1 SND225048C1000    EAC Certificate:  UR_S020042    UR Certificate:  UR_S020042    UR Certificate:  UR_E352056    Classifications  Object Classification Code:    Object Classification Code:  K    ETIM 4:  EC001437 - Switching relay    ETIM 5:  EC001437 - Switching relay    ETIM 5:  EC001437 - Switching relay    UNSPSC:  39121500	Package Level 1 Gross Weight:	0.23 kg
Function:  Boxed interface relay R600    Sub-Function:  Relay with built in LED    Output:  1 c/o (SPDT) contact    Output Signal:  12 250 V AC / 10 mA 6 A    Rated Control Supply Voltage (U <sub>5</sub> ):  12 V DC    Terminal Type:  Spring Terminals    Certificates and Declarations (Document Number)  CSA Certificate:    CSA Certificate:  CSA_254821    cUR Certificate:  cUR_E352056    Declaration of Conformity - CE:  1SND225048C1000    EAC Certificate:  EAC_RU_C-FR.ME77.B.01634    LR Certificate:  UR_E352056    Classifications  UR_E352056    Object Classification Code:  K    ETIM 4:  EC001437 - Switching relay    ETIM 5:  EC001437 - Switching relay    UNSPSC:  39121500	Package Level 1 EAN:	3472596455354
Sub-Function:Relay with built in LEDOutput:1 c/o (SPDT) contactOutput Signal:12 250 V AC / 10 mA 6 ARated Control Supply Voltage (Us):12 V DCTerminal Type:Spring TerminalsCertificates and Declarations (Document Number)CSA Certificate:CSA_254821cUR Certificate:cUR_E352056Declaration of Conformity - CE:1SND225048C1000EAC Certificate:EAC_RU_C-FR.ME77.B.01634LR Certificate:UR_E352056Object Classifications Code:KETIM 4:EC001437 - Switching relayETIM 5:EC001437 - Switching relayUNSPSC:39121500	Technical	
Output:1 c/o (SPDT) contactOutput Signal:12 250 V AC / 10 mA 6 ARated Control Supply Voltage (Us):12 V DCTerminal Type:Spring TerminalsCertificates and Declarations (Document Number)CSA Certificate:CSA Certificate:CSA_254821cUR Certificate:cUR_E352056Declaration of Conformity - CE:1SND225048C1000EAC Certificate:EAC_RU_C-FR.ME77.B.01634LR Certificate:UR_E352056Object ClassificationsUR_E352056Object Classification Code:KETIM 4:EC001437 - Switching relayETIM 5:EC001437 - Switching relayUNSPSC:39121500	Function:	Boxed interface relay R600
Output Signal:  12 250 V AC / 10 mA 6 A    Rated Control Supply Voltage (Us):  12 V DC    Terminal Type:  Spring Terminals    Certificates and Declarations (Document Number)  CSA Certificate:    CSA Certificate:  CSA_254821    cUR Certificate:  cUR_E352056    Declaration of Conformity - CE:  1SND225048C1000    EAC Certificate:  EAC_RU_C-FR.ME77.B.01634    LR Certificate:  UR_E352056    UR Certificate:  UR_E352056    Object Classifications  VILT_C-FR.ME77.B.01634    Classifications  VILT_E352056    Object Classification Code:  K    ETIM 4:  EC001437 - Switching relay    ETIM 5:  EC001437 - Switching relay    UNSPSC:  39121500	Sub-Function:	Relay with built in LED
Rated Control Supply Voltage (Us):  12 V DC    Terminal Type:  Spring Terminals    Certificates and Declarations (Document Number)    CSA Certificate:  CSA_254821    cUR Certificate:  cUR_E352056    Declaration of Conformity - CE:  1SND225048C1000    EAC Certificate:  EAC_RU_C-FR.ME77.B.01634    LR Certificate:  UR_E352056    UR Certificate:  UR_E352056    Object Classifications  UR_E352056    Classifications  VR_E352056    UR Certificate:  UR_E352056    Classifications  UR_E352056    Classifications  UR_E352056    UNSPSC:  Switching relay    UNSPSC:  39121500	Output:	1 c/o (SPDT) contact
Terminal Type:Spring TerminalsCertificates and Declarations (Document Number)CSA Certificate:CSA_254821cUR Certificate:cUR_E352056Declaration of Conformity - CE:1SND225048C1000EAC Certificate:EAC_RU_C-FR.ME77.B.01634LR Certificate:UR_S0620042UR Certificate:UR_E352056ClassificationsObject Classification Code:KETIM 4:EC001437 - Switching relayETIM 5:EC001437 - Switching relayUNSPSC:39121500		
Certificates and Declarations (Document Number)    CSA Certificate:  CSA_254821    cUR Certificate:  cUR_E352056    Declaration of Conformity - CE:  1SND225048C1000    EAC Certificate:  EAC_RU_C-FR.ME77.B.01634    LR Certificate:  LRS_0620042    UR Certificate:  UR_E352056    Classifications  UR_E352056    Object Classification Code:  K    ETIM 4:  EC001437 - Switching relay    ETIM 5:  EC001437 - Switching relay    UNSPSC:  39121500	Rated Control Supply Voltage (Us):	12 V DC
CSA Certificate:CSA_254821cUR Certificate:cUR_E352056Declaration of Conformity - CE:1SND225048C1000EAC Certificate:EAC_RU_C-FR.ME77.B.01634LR Certificate:LRS_0620042UR Certificate:UR_E352056ClassificationsObject Classification Code:KETIM 4:EC001437 - Switching relayETIM 5:EC001437 - Switching relayUNSPSC:39121500	Terminal Type:	Spring Terminals
CSA Certificate:CSA_254821cUR Certificate:cUR_E352056Declaration of Conformity - CE:1SND225048C1000EAC Certificate:EAC_RU_C-FR.ME77.B.01634LR Certificate:LRS_0620042UR Certificate:UR_E352056ClassificationsObject Classification Code:KETIM 4:EC001437 - Switching relayETIM 5:EC001437 - Switching relayUNSPSC:39121500	Certificates and Declarations (D	ocument Number)
cUR Certificate:cUR_E352056Declaration of Conformity - CE:1SND225048C1000EAC Certificate:EAC_RU_C-FR.ME77.B.01634LR Certificate:LRS_0620042UR Certificate:UR_E352056ClassificationsObject Classification Code:KEC001437 - Switching relayETIM 4:EC001437 - Switching relayUNSPSC:39121500	· · · · · · · · · · · · · · · · · · ·	•
Declaration of Conformity - CE:  1SND225048C1000    EAC Certificate:  EAC_RU_C-FR.ME77.B.01634    LR Certificate:  LRS_0620042    UR Certificate:  UR_E352056    Classifications    Object Classification Code:  K    ETIM 4:  EC001437 - Switching relay    ETIM 5:  EC001437 - Switching relay    UNSPSC:  39121500		-
EAC Certificate:EAC_RU_C-FR.ME77.B.01634LR Certificate:LRS_0620042UR Certificate:UR_E352056ClassificationsObject Classification Code:KETIM 4:EC001437 - Switching relayETIM 5:EC001437 - Switching relayUNSPSC:39121500		-
LR Certificate:  LRS_0620042    UR Certificate:  UR_E352056    Classifications    Object Classification Code:  K    ETIM 4:  EC001437 - Switching relay    ETIM 5:  EC001437 - Switching relay    UNSPSC:  39121500	-	
UR Certificate:  UR_E352056    Classifications  Classification Code:    Object Classification Code:  K    ETIM 4:  EC001437 - Switching relay    ETIM 5:  EC001437 - Switching relay    UNSPSC:  39121500	LR Certificate:	
Object Classification Code:  K    ETIM 4:  EC001437 - Switching relay    ETIM 5:  EC001437 - Switching relay    UNSPSC:  39121500	UR Certificate:	
ETIM 4:    EC001437 - Switching relay      ETIM 5:    EC001437 - Switching relay      UNSPSC:    39121500	Classifications	
ETIM 5:    EC001437 - Switching relay      UNSPSC:    39121500	Object Classification Code:	К
<b>UNSPSC:</b> 39121500	ETIM 4:	EC001437 - Switching relay
	ETIM 5:	EC001437 - Switching relay
eClass: 7.0 27371601	UNSPSC:	39121500
	eClass:	7.0 27371601







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product	Code	Reference	Product link
RBR121-12VDC Interface relay R600 1c/o,A1- A2=12VDC,250V/10mA-6A, LED	1SNA645535R2600	RBR 121-12VDC	Buy on EAN