



Automatización Eléctrica Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking <u>HERE</u>

CR-M120AC4L



General Information

Extended Product Type:	CR-M120AC4L
Product ID:	1SVR405613R2100
EAN:	4013614497742
Catalog Description:	CR-M120AC4L Pluggable interface relay 4c/o, A1-A2=120VAC, 250V/6A, LED
Long Description:	The CR-M120AC4L pluggable interface relay is from the CR-M (miniature) relay range. This relay operates with a 120 V AC rated control supply voltage and has a 4 c/o (SPDT) output with contacts rated at 250 V / 6 A. The relay has an integrated orange test button for manual actuation and locking of the output contacts and an integrated LED. Standard sockets, logic sockets, pluggable function modules, holder and marker are available as accessories.

Categories

Products » Low Voltage Products and Systems » Control Products » Electronic Relays and Controls » Interface Relays and Optocouplers

Ordering	
EAN:	4013614497742
Minimum Order Quantity:	10 piece
Customs Tariff Number:	85364900
Dimensions	
Product Net Width:	21.2 mm
Product Net Height:	35.6 mm
Product Net Depth:	27.5 mm
Product Net Weight:	0.033 kg
Floduct Net Weight.	0.000 kg
Container Information	
Package Level 1 Units:	10 piece
Package Level 1 Width:	114 mm
Package Level 1 Height:	61 mm
Package Level 1 Length:	50 mm
Package Level 1 Gross Weight:	0.35 kg
Package Level 1 EAN:	4013614373640
Teshuisel	
Technical Function:	Diversible ministure interface rales CD M
Sub-Function:	Pluggable miniature interface relay CR-M
	Relay with built in LED
Output:	4 c/o (SPDT) contacts
Output Signal:	250 V / 6 A
Rated Control Supply Voltage (U _s):	
Environmental	
RoHS Status:	Following EU Directive 2011/65/EC
Certificates and Declarations (De	ocument Number)
CCC Certificate:	CCC 2014010303720193
CSA Certificate:	CSA 2735700
cUR Certificate:	 cUR_E244330
Declaration of Conformity - CE:	
EAC Certificate:	EAC_RU_C-PL.ME77.B.01873
GOST Certificate:	GOST_POCC_DE.AB76.D02256
LR Certificate:	LR_05_20002_E3
RMRS Certificate:	RMRS_12.04008.250
RoHS Information:	1SAA981040-4404
UR Certificate:	UR_E244330
VDE Certificate:	VDE_40040327
Classifications	
Classifications	K
Object Classification Code:	K EC001/137 - Switching relay
Object Classification Code: ETIM 4:	EC001437 - Switching relay
Object Classification Code: ETIM 4: ETIM 5:	EC001437 - Switching relay EC001437 - Switching relay
Object Classification Code: ETIM 4:	EC001437 - Switching relay

eClass:

7.0 27371601





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product	Code	Reference	Product link
CR-M120AC4L Pluggable interface relay 4c/o, A1-A2=120VAC, 250V/6A, LED	1SVR405613R2100	CR- M120AC4L	Buy on EAN