



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

Extended Product Type:	CM-MSS.51S
Product ID:	1SVR730712R1300
EAN:	4013614496660
Catalog Description:	CM-MSS.51S Therm. motor protec. relay 2x1c/o, 24-240VAC/DC
Long Description:	The CM-MSS.51S belongs to the CM thermistor motor protection relay range. It operates with a rated control supply voltage of 24 - 240 V AC / DC and has a 2 c/o (SPDT) output with contacts rated at 250 V / 4 A. It features two sensor circuit to monitor PTC temperature sensors (single or accumulative evaluation, configurable) and works according to the closed-circuit principle. The sensor circuits of this CM-MSS.51S are short-circuit (configurable), as well as interrupted-wire monitored and can be reset automatically, manually or remotely after the failure has been removed. This protection relay is certified according to the ATEX directive 49/9/EC and is equipped with a reset / test button. The non-volatile fault storage, the short circuit detection and the accumulative evaluation can be enabled/disabled via DIP switches. A sealable transparent cover for protection against unauthorized changes is available as accessory. The device offers screw connection technology with double-chamber cage connection terminals.

Categories

Products » Low Voltage Products and Systems » Control Products » Electronic Relays and Controls » Thermistor Motor Protection Relays

Ordering

EAN:	4013614496660
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85364900

Dimensions

Product Net Width:	22.5 mm
Product Net Height:	85.6 mm
Product Net Depth:	103.7 mm
Product Net Weight:	0.145 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	97 mm
Package Level 1 Height:	109 mm
Package Level 1 Length:	30 mm
Package Level 1 Gross Weight:	0.172 kg

Technical

Function:	2 sensor circuits Short-circuit detection, configurable Non-volatile fault storage, configurable Single or accumulative evaluation, configurable Dynamic interrupted wire detection Auto, manual or remote reset ATEX approved
Rated Control Supply Voltage (U_s):	24 ... 240 V AC/DC
Output:	2 x 1 c/o or 1 x 2 c/o contacts, configurable
Terminal Type:	Screw Terminals
Rated Operational Current AC-12 (I_e):	(230 V) 4 A
Rated Operational Current AC-15 (I_e):	(230 V) 3 A
Rated Operational Current DC-12 (I_e):	(24 V) 4 A
Rated Operational Current DC-13 (I_e):	(24 V) 2 A
Minimum Switching Capacity:	24 V 10 mA
Rated Insulation Voltage (U_i):	300 V Measuring Circuit / Output Circuit 300 V Output Circuit 1 / Output Circuit 2 300 V Supply Circuit / Measuring Circuit 300 V Supply Circuit / Output Circuit 300 V

Rated Impulse Withstand Voltage (U_{imp}):	Output Circuit 1 / Output Circuit 2 4 kV Output Circuit 4 kV
Degree of Protection:	Housing IP50 Terminals IP20
Overvoltage Category:	III
Pollution Degree:	3
Short-Circuit Protective Devices:	Output Circuit NC - F Type Fuses 6 A Output Circuit NO - F Type Fuses 10 A
Electrical Durability:	AC-12 100000 cycle
Mechanical Durability:	30000000 cycle
Connecting Capacity:	Flexible 1x 0.5 ... 2.5 mm ² Flexible 2x 0.5 ... 1.5 mm ² Rigid 1x 0.5 ... 4 mm ² Rigid 2x 0.5 ... 2.5 mm ²
Tightening Torque:	0.6 ... 0.8 N·m
Wire Stripping Length:	8 mm
Mounting Position:	Any
Mounting on DIN Rail:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Standards:	IEC/EN 60947-8 UL 508 CSA 22.2 No. 14

Environmental

Ambient Air Temperature:	Operation -25 ... +60 °C Storage -40 ... +85 °C
RoHS Status:	Following EU Directive 2011/65/EC

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Output Circuit 300 V AC
Contact Rating UL/CSA:	B300
Connecting Capacity UL/CSA:	Flexible 1x 18 ... 14 AWG Flexible 2x 18 ... 16 AWG Rigid 1x 20 ... 12 AWG Rigid 2x 20 ... 14 AWG
Tightening Torque UL/CSA:	7.08 in·lb

Certificates and Declarations (Document Number)

ATEX Certificate:	EC Type Examination Certificate_TPS_14_ATEX_44254_005_X
CB Certificate:	CB_DK-40837-UL
CCC Certificate:	CCC_2005010303165479
cULus Certificate:	cULus508_20140912-E140448
Declaration of Conformity - CE:	1SAD938500-0220
EAC Certificate:	EAC_RU_C-DE.ME77.B.01825
GL Certificate:	GL_13759-14HH
RoHS Information:	1SAA981070-4401

Classifications

Object Classification Code:	B
ETIM 5:	EC001446 - Temperature monitoring relay
eClass:	7.0 27371810





Automatización Eléctrica
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
CM-MSS.51S Therm. motor protec. relay 2x1c/o, 24-240VAC/DC	1SVR730712R1300	CM-MSS.51S	Buy on EAN