



**Automatización Eléctrica**

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

## General Information

|                        |   |
|------------------------|---|
| Extended Product Type: | S802B-C32   |
| Product ID:            | 2CCS812001R0324   |
| EAN:                   | 7612271416232   |
| Catalog Description:   | S802B-C32 High Performance Circuit Breaker  |
| Long Description:      | The S802B-C32 is a 2-pole High Performance Circuit breaker with C-characteristic, with cage terminal and a rated current of 32 A. It is a current limiting device with a maximum breaking capacity of 16kA at 230/400V. It can be used for voltages up to 230/400V. It has two different tripping mechanisms, the thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. The S802B-C32 complies with IEC/EN 60947-2 and EN 60898-1 and allows the use for residential, commercial and industrial applications. It has numerous of approvals, therefore it can be used worldwide. The extensive range of accessory makes the use of S802B-C32 more comfortable. Due to the fast arc extinction of S802B-C32 your application will be secured. |

## Categories

Products » Low Voltage Products and Systems » Modular DIN Rail Products » High Performance Circuit Breakers HPCBs

## Ordering

|                         |               |
|-------------------------|---------------|
| EAN:                    | 7612271416232 |
| Minimum Order Quantity: | 1 piece       |
| Customs Tariff Number:  | 85362020      |

## Dimensions

|                     |         |
|---------------------|---------|
| Product Net Width:  | 54 mm   |
| Product Net Depth:  | 82.5 mm |
| Product Net Height: | 95 mm   |
| Product Net Weight: | 0.49 kg |

## Container Information

|                               |               |
|-------------------------------|---------------|
| Package Level 1 Units:        | 1 piece       |
| Package Level 1 Width:        | 105 mm        |
| Package Level 1 Length:       | 60 mm         |
| Package Level 1 Height:       | 99 mm         |
| Package Level 1 Gross Weight: | 0.51 kg       |
| Package Level 1 EAN:          | 7612271416232 |
| Package Level 2 Units:        | 1 piece       |
| Package Level 2 Height:       | 0.92 mm       |
| Package Level 2 Gross Weight: | 0.51 kg       |

## Environmental

|                          |   |
|--------------------------|---|
| Ambient Air Temperature: | Operation -25 ... +60 °C<br>Storage -40 ... +70 °C              |
| RoHS Status:             | Following EU Directive 2002/95/EC August 18, 2005 and amendment |

## Technical

|  |  |
|--|--|
| Standards:   | IEC/EN 60947-2 IEC/EN 60898-1                |
| Number of Poles:   | 2  |
| Tripping Characteristic:                                     | C  |
| Rated Current ( $I_n$ ):                                     | 32 A   |
| Rated Operational Voltage:                                   | 230/400 V AC<br>75 V DC                      |
| Power Loss:  | at Rated Operating Conditions per Pole 3.2 W |
| Rated Insulation Voltage ( $U_i$ ):                          | 440 V AC                                     |
| Rated Frequency (f):   | 50 / 60 Hz                                   |
| Rated Short-Circuit Capacity ( $I_{cn}$ ):                   | 10 kA  |
| Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ ): | (230 / 400 V AC) 16 kA                       |
| Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ ):  | (230 / 400 V AC) 10 kA                       |
| Overvoltage Category:  | III  |
| Pollution Degree:  | 3  |
| Rated Impulse Withstand Voltage                              | 4 kV   |

|                                     |  |
|-------------------------------------|--|
| <b>(U<sub>imp</sub>):</b>           |  |
| <b>Housing Material:</b>            | Insulation group I, RAL 7035   |
| <b>Contact Position Indication:</b> | ON / OFF / TRIP  |
| <b>Degree of Protection:</b>        | acc. to IEC 60529 IP20   |
| <b>Remarks:</b>                     | Connection from top and bottom<br>Connecting with CU only<br>IP40 in enclosure with cover<br>Cage terminal with captille screw |
| <b>Terminal Type:</b>               | Screw Terminals  |
| <b>Connecting Capacity:</b>         | Flexible 1 ... 50 mm <sup>2</sup><br>Flexible Stranded<br>1 ...70 mm <sup>2</sup>  |
| <b>Tightening Torque:</b>           | 3.5 N·m  |
| <b>Recommended Screw Driver:</b>    | Pozidriv 2   |
| <b>Mounting on DIN Rail:</b>        | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715<br>TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715                 |
| <b>Mounting Position:</b>           | Any  |

#### Certificates and Declarations (Document Number)

|  |                 |
|--|-----------------|
| <b>Declaration of Conformity - CE:</b> | 2CCC413016D060  |
| <b>RoHS Information:</b>               | 2CCC413008D0204 |

#### Classifications

|                                    |  |
|------------------------------------|--|
| <b>ETIM 4:</b>                     | EC000042 - Miniature circuit breaker (MCB) |
| <b>ETIM 5:</b>                     | EC000042 - Miniature circuit breaker (MCB) |
| <b>Object Classification Code:</b> | F  |





**Automatización Eléctrica**  
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

| Product                                    | Code            | Reference | Product link               |
|--|-----------------|-----------|----------------------------|
| S802B-C32 High Performance Circuit Breaker | 2CCS812001R0324 | S802B-C32 | <a href="#">Buy on EAN</a> |