



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking <u>HERE</u>

# S802S-UCK50



### **General Information**

 Extended Product Type:
 \$802\$S-UCK50

 Product ID:
 2CC\$862001R1577

 EAN:
 7612271203511

Catalog Description: High Performance Circuit Breaker - S800S - Tripping characteristic K - Number of poles 2 -

Rated operational current 50A - Rated operational voltage 250V DC

Long Description: S802S-UCK50 High Performance Miniature Circuit Breaker 2 Poles K Characteristic 50A

50kA 250VDC

### Categories

Products » Low Voltage Products and Systems » Modular DIN Rail Products » High Performance Circuit Breakers HPCBs

#### Ordering

 EAN:
 7612271203511

 Minimum Order Quantity:
 1 piece

 Customs Tariff Number:
 85362020

### **Dimensions**

Product Net Width:54 mmProduct Net Depth:82.5 mmProduct Net Height:95 mmProduct Net Weight:0.49 kg

### **Container Information**

Package Level 1 Units:1 piecePackage Level 1 Width:105 mmPackage Level 1 Length:60 mmPackage Level 1 Height:99 mmPackage Level 1 Gross Weight:0.51 kgPackage Level 1 EAN:7612271203511Package Level 2 Units:1

### **Environmental**

Ambient Air Temperature: Operation -25 ... +60 °C

Storage -40 ... +70 °C

RoHS Status: Following EU Directive 2002/95/EC August 18, 2005 and amendment

### **Technical**

Standards: IEC/EN 60947-2 **Number of Poles:** 2 Tripping Characteristic: UC-K 50 A Rated Current (In): Rated Operational Voltage: 500 V DC Power Loss: 8.6 W **Rated Ultimate Short-Circuit** (500 V DC) 50 kA Breaking Capacity (Icu): Rated Service Short-Circuit (500 V DC) 50 kA Breaking Capacity (I<sub>cs</sub>): **Contact Position Indication:** ON / OFF / TRIP Flexible 1 ... 50 mm<sup>2</sup> **Connecting Capacity:** Flexible Stranded 1 ...70 mm<sup>2</sup>

### Certificates and Declarations (Document Number)

 Declaration of Conformity - CE:
 2CCC413016D0601

 RoHS Information:
 2CCC413008D0201

## Classifications

Object Classification Code:	F
ETIM 5:	EC000042 - Miniature circuit breaker (MCB)
ETIM 4:	EC000042 - Miniature circuit breaker (MCB)







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
High Performance Circuit Breaker - S800S - Tripping characteristic K - Number of poles 2 - Rated operational current 50A - Rated operational voltage 250V DC	2CCS862001R1577	S802S- UCK50	Buy on EAN