



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking <u>HERE</u>

S803S-UCK32



General Information

 Extended Product Type:
 \$803\$-UCK32

 Product ID:
 2CC\$863001R1537

 EAN:
 7612271203610

Catalog Description: High Performance Circuit Breaker - S800S - Tripping characteristic K - Number of poles 3 -

Rated operational current 32A - Rated operational voltage 750V DC

Long Description: S803S-UCK32 High Performance Miniature Circuit Breaker 3 Poles K Characteristic 32A

50kA 250VDC

Categories

Products » Low Voltage Products and Systems » Modular DIN Rail Products » High Performance Circuit Breakers HPCBs

Ordering

 EAN:
 7612271203610

 Minimum Order Quantity:
 1 piece

 Customs Tariff Number:
 85362020

Dimensions

Product Net Width: 81 mm

Product Net Depth: 82.5 mm

Product Net Height: 95 mm

Product Net Weight: 0.74 kg

Container Information

Package Level 1 Units:1 piecePackage Level 1 Width:105 mmPackage Level 1 Length:86 mmPackage Level 1 Height:99 mmPackage Level 1 Gross Weight:0.77 kgPackage Level 1 EAN:7612271203610Package Level 2 Units:1

Environmental

Ambient Air Temperature: Operation -25 ... +60 °C

Storage -40 ... +70 °C

RoHS Status: Following EU Directive 2002/95/EC August 18, 2005 and amendment

Technical

Standards: IEC/EN 60947-2 **Number of Poles:** 3 Tripping Characteristic: UC-K 32 A Rated Current (In): Rated Operational Voltage: 750 V DC Power Loss: 9.3 W **Rated Ultimate Short-Circuit** (750 V DC) 50 kA Breaking Capacity (Icu): Rated Service Short-Circuit (750 V DC) 50 kA Breaking Capacity (I_{cs}): **Contact Position Indication:** ON / OFF / TRIP Flexible 1 ... 50 mm² **Connecting Capacity:** Flexible Stranded 1 ...70 mm²

Certificates and Declarations (Document Number)

 Declaration of Conformity - CE:
 2CCC413016D0601

 RoHS Information:
 2CCC413008D0201

Classifications

Object Classification Code:	F
ETIM 5:	EC000042 - Miniature circuit breaker (MCB)
ETIM 4:	EC000042 - Miniature circuit breaker (MCB)







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
High Performance Circuit Breaker - S800S - Tripping characteristic K - Number of poles 3 - Rated operational current 32A - Rated operational voltage 750V DC	2CCS863001R1537	S803S- UCK32	Buy on EAN