



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

| | |
|------------------------|--|
| Extended Product Type: | S803C-D125 |
| Product ID: | 2CCS883001R0841 |
| EAN: | 7612271213947 |
| Catalog Description: | S803C-D125 High Performance Circuit Breaker |
| Long Description: | The S803C-D125 is a 3-pole High Performance Circuit breaker with D-Characteristic, with cage terminal and a rated current of 125 A. It is a current limiting device with a maximum breaking capacity of 25kA at 240/415V. It can be used for voltages up to 254/440V and in DC as well. It has two different tripping mechanisms, the thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. The S803C-D125 complies with IEC/EN 60898-1 and IEC/EN 60947-2 and allows the use for industrial applications. It has numerous of approvals, therefore it can be used worldwide. The extensive range of accessory makes the use of S803C-D125 more comfortable. Due to the fast arc extinction of S803C-D125 your application will be secured. |

Categories

Products » Low Voltage Products and Systems » Modular DIN Rail Products » High Performance Circuit Breakers HPCBs

Ordering

| | |
|-------------------------|---------------|
| EAN: | 7612271213947 |
| Minimum Order Quantity: | 1 piece |
| Customs Tariff Number: | 85362020 |

Dimensions

| | |
|---------------------|---------|
| Product Net Width: | 81 mm |
| Product Net Depth: | 82.5 mm |
| Product Net Height: | 95 mm |
| Product Net Weight: | 0.74 kg |

Container Information

| | |
|-------------------------------|---------------|
| Package Level 1 Units: | 1 piece |
| Package Level 1 Width: | 105 mm |
| Package Level 1 Length: | 86 mm |
| Package Level 1 Height: | 99 mm |
| Package Level 1 Gross Weight: | 0.77 kg |
| Package Level 1 EAN: | 7612271213947 |

Environmental

| | |
|---|---|
| Ambient Air Temperature: | Operation -25 ... +60 °C Storage -40 ... +70 °C |
| Resistance to Shock acc. to IEC 60068-2-27: | 5 g 30 ms |
| Resistance to Vibrations acc. to IEC 60068-2-6: | 2 - 13.2 Hz / 1mm 13.2 - 100Hz / 0.7g with load 100% x le |
| Environmental Conditions: | Damp Heat Cyclic acc. to IEC 60068-2-30 12+12 cycle Damp Heat Cyclic acc. to IEC 60068-2-30 55°C @ 90-96% Damp Heat Cyclic acc. to IEC 60068-2-30 25°C @ 90-100% Dry Heat Test B acc. to IEC 60068-2-2 16 hour @ 55 °C Dry Heat Test B acc. to IEC 60068-2-2 2 hour @ 70 °C |
| RoHS Status: | Following EU Directive 2002/95/EC August 18, 2005 and amendment |

Technical

| | |
|---|--|
| Standards: | IEC/EN 60947-2 IEC/EN 60898-1 |
| Number of Poles: | 3 |
| Tripping Characteristic: | D |
| Rated Current (I _n): | 125 A |
| Rated Operational Voltage: | 254/440 V |
| Power Loss: | at Rated Operating Conditions per Pole 9.4 W |
| Rated Insulation Voltage (U _i): | 500 V AC |
| Operational Voltage: | Maximum 230/400 V AC Minimum 12 V AC |
| Rated Frequency (f): | 50 / 60 Hz |
| Rated Ultimate Short-Circuit | (240 / 415 V AC) 50 kA (254 / 440 V AC) 30 kA |

| | |
|---|---|
| Breaking Capacity (I_{cu}): | (400 / 690 V AC) 4.5 kA (125 V DC) 30 kA |
| Rated Service Short-Circuit Breaking Capacity (I_{cs}): | (240 / 415 V AC) 40 kA (254 / 440 V AC) 15 kA (400 / 690 V AC) 4 kA (125 V DC) 30 kA |
| Energy Limiting Class: | 3 |
| Overvoltage Category: | IV |
| Pollution Degree: | 3 |
| Rated Impulse Withstand Voltage (U_{imp}): | 8 kV |
| Housing Material: | Insulation group I, RAL 7035 |
| Contact Position Indication: | ON / OFF / TRIP |
| Degree of Protection: | acc. to IEC 60529 IP20 |
| Remarks: | Connection from top and bottom Connecting with CU only IP40 in enclosure with cover Cage terminal with captive screw |
| Electrical Endurance: | 4000 cycle |
| Mechanical Endurance: | 6000 cycle |
| Terminal Type: | Screw Terminals |
| Connecting Capacity: | Stranded 1 ... 50 mm ² Flexible 1 ... 70 mm ² |
| Tightening Torque: | 3.5 N·m 31 in·lb |
| Recommended Screw Driver: | Pozidriv 2 |
| Mounting on DIN Rail: | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 |
| Mounting Position: | Any |

Certificates and Declarations (Document Number)

| | |
|--|-----------------|
| Declaration of Conformity - CE: | 2CCC413016D060 |
| RoHS Information: | 2CCC413008D0204 |

Classifications

| | |
|------------------------------------|--|
| ETIM 4: | EC000042 - Miniature circuit breaker (MCB) |
| ETIM 5: | EC000042 - Miniature circuit breaker (MCB) |
| Object Classification Code: | F |





Automatización Eléctrica
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

| Product | Code | Reference | Product link |
|---|-----------------|------------|----------------------------|
| S803C-D125 High Performance Circuit Breaker | 2CCS883001R0841 | S803C-D125 | Buy on EAN |