



## Automatización Eléctrica Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking <u>HERE</u>

## F204 B-25/0,3



## General Information

Extended Product Type:	F204 B-25/0,3
Product ID:	2CSF204592R3250
EAN:	8012542347934
Catalog Description:	F204 B-25/0,3 Residual Current Dev.
Long Description:	The RCCBs F200 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous and selective AC and A types is completed with some configurations for special applications. This product is particularly suitable for the protection against smooth d.c. earth fault currents.

## Categories

Products » Low Voltage Products and Systems » Modular DIN Rail Products » Residual Current Devices RCDs » Residual Current Devices RCDs

EAN:	8012542347934
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85363030
Dimensions	
Product Net Width:	0.072 m
Product Net Height:	0.085 m
Product Net Depth:	0.069 m
Product Net Weight:	0.500 kg
Container Information	
Package Level 1 Units:	1 piece
Package Level 1 Width:	0.073 m
Package Level 1 Height:	0.078 m
Package Level 1 Length:	0.09 m
Package Level 1 Gross Weight:	0.525 kg
Package Level 1 EAN:	8012542347934
Technical	
Standards:	EN 61008
Operating Characteristic:	he standard and a standard and
Operating characteristic.	Instantaneous
Type of Residual Current:	B type
Type of Residual Current:	B type
Type of Residual Current: Rated Residual Current:	B type 300 mA
Type of Residual Current: Rated Residual Current: Rated Current (I <sub>n</sub> ):	B type 300 mA 25 A
Type of Residual Current: Rated Residual Current: Rated Current (I <sub>n</sub> ): Number of Poles:	B type 300 mA 25 A 4
Type of Residual Current: Rated Residual Current: Rated Current (I <sub>n</sub> ): Number of Poles: Position of Neutral Terminals:	B type 300 mA 25 A 4 Right at Rated Operating Conditions per Pole 0.29 W
Type of Residual Current: Rated Residual Current: Rated Current (I <sub>n</sub> ): Number of Poles: Position of Neutral Terminals: Power Loss:	B type 300 mA 25 A 4 Right at Rated Operating Conditions per Pole 0.29 W
Type of Residual Current: Rated Residual Current: Rated Current (I <sub>n</sub> ): Number of Poles: Position of Neutral Terminals: Power Loss: Certificates and Declarations (I	B type 300 mA 25 A 4 Right at Rated Operating Conditions per Pole 0.29 W Document Number)
Type of Residual Current: Rated Residual Current: Rated Current (I <sub>n</sub> ): Number of Poles: Position of Neutral Terminals: Power Loss: Certificates and Declarations (I Declaration of Conformity - CE:	B type 300 mA 25 A 4 Right at Rated Operating Conditions per Pole 0.29 W Document Number) 2CSC423009D2701
Type of Residual Current: Rated Residual Current: Rated Current (I <sub>n</sub> ): Number of Poles: Position of Neutral Terminals: Power Loss: Certificates and Declarations (I Declaration of Conformity - CE: RoHS Information:	B type 300 mA 25 A 4 Right at Rated Operating Conditions per Pole 0.29 W Document Number) 2CSC423009D2701
Type of Residual Current: Rated Residual Current: Rated Current (I <sub>n</sub> ): Number of Poles: Position of Neutral Terminals: Power Loss: Certificates and Declarations (I Declaration of Conformity - CE: RoHS Information: Classifications	B type 300 mA 25 A 4 Right at Rated Operating Conditions per Pole 0.29 W Document Number) 2CSC423009D2701 2CSC423006K2701







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product	Code	Reference	Product link
F204 B-25/0,3 Residual Current Dev.	2CSF204592R3250	F204B-25/0,3	Buy on EAN